

5 BLM 1 File 1 Celsius-Den 1 Celsius-SLC
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. GIFT AGREEMENT NAME	
2. NAME OF OPERATOR		8. IF INDIAN, ALLOTTEE OR TRIBE NAME	
DUGAN PRODUCTION CORP.		20	
3. ADDRESS OF OPERATOR		9. AREA	
P.O. Box 208, Farmington, NM 87499		FARMINGTON RESOURCE AREA	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface		10. FIELD OR LEASE NAME	
810' FSL & 810' FWL		Olympic	
14. PERMIT NO.		11. WELL NO.	
15. ELEVATIONS (Show whether OF, RT, CR, etc.)		12. FIELD AND POOL, OR WILDCAT	
6665' GL; 6677' RKB		South Bisti Gallup	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA	
		Sec. 3, T23N, R10W, NMPM	
		12. COUNTY OR PARISH	
		San Juan	
		13. STATE	
		NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACURE TREAT	☐	FRACURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other) <u>Spud, Surface Casing & Test</u>	☒
(Other)	☐	(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

M.I. & R.U. Four Corners
Drilling Company Rig #5. Spudded a 12 $\frac{1}{4}$ " hole @ 11:30 A.M. on 1-22-88. Drilled to 224'.
Ran 5 jts. 8-5/8" OD, 32#, 8 Rd, ST&C casing (T.E. = 201') set @ 213'. Cemented w/ 135 sx class "B" + 2% CaCl₂ (total cement slurry = 159 cf).
Circulated 1/2 bbl good cement to surface. P.O.B. @ 3:15 PM 1-22-88.

Pressure tested B.O.P. & surface casing to 600 psi 30 minutes before drilling out - held OK.

I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs TITLE Geologist DATE 1-25-88
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE FEB 02 1988
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

FARMINGTON RESOURCE AREA