

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.		8. FARM OR LEASE NAME Champ	
3. ADDRESS OF OPERATOR P.O. Box 5820, Farmington, NM 87499-5820		9. WELL NO. 2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL & 660' FWL		10. FIELD AND POOL, OR WILDCAT South Bisti Gallup	
14. PERMIT NO.		11. SPC, T, R, M, OR BLK. AND SURVEY OR AREA Sec. 5, T23N, R10W, NMPM	
15. ELEVATIONS (Show whether OF, FT, OR, etc.) 6568' GL'; 6580' RKB		12. COUNTY OR PARISH San Juan	
		13. STATE NM	

6. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACURE TREAT	☐	FRACURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other) <u>Spud & Surface Casing</u>	☒
(Other)	☐	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Moved in & rigged up Four Corners Drilling Company Rig #9. Spudded a 12 1/4" hole @ 3:15 PM 8-24-88. Drilled to 228'. Ran 7 jts. - 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 206.78') set @ 219' RKB. Cemented with 135 sx class "B" + 2% CaCl₂ (total cement slurry 159 cu. ft.). Circulated 2 bbls cement to surface. P.O.B. @ 12:00 midnight 8-24-88.

Pressure tested surface casing and BOP 600 psi for 30 minutes before drilling cement and shoe - held OK.

RECEIVED
SEP 1 - 1988
OIL CON. DIV.
DIST. 3

I hereby certify that the foregoing is true and correct

SIGNED <u>Jim K. Jacobs</u>	TITLE <u>Geologist</u>	DATE <u>8-26-88</u>
(This space for Federal or State office use)		
APPROVED BY _____	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		