(November 1983) (Formerly 9-331) DEPARTM	INITED STATES IENT OF THE INTER	1 Celsius-Denver SUBMIT IN TRIPLICAT (Other Instructions on	Expires August 5. LEARE DESIGNATION	AND BREIAL NO.	
BUREAU OF LAND MANAGEMENT				NOO-C-14-20-7307	
SUNDRY NOTION OF THE CONTROL OF THE	CES AND REPORTS (Is to drill or to deepen or plug (TION FOR PERMIT—" for such p	ON WELLS VE	Navajo Allott		
1. OIL V GAB		88 DEC 22 AH (0: 58	7. UNIT AGREEMENT NA	.ME	
WELL IN WELL I OTHER			8. FARM OR LEASE NAME		
DUGAN PRODUCTION CORP. FARMINGTON RESOURCE AREA FARMINGTON, NEW MEXICO			Bronze Meda	Bronze Medal	
3. ADDRESS OF OPERATOR			9. WELL NO.		
P.O. Box 5820, Farming 1. LOCATION OF WELL (Report location cle	2 10. FIELD AND POOL, O	R WILDCAT			
See also space 17 selow.) At surface		South-Bisti Gallup			
1830' FNL 3 670' FWL	SURVEY OR ARMA	Sec. 3, T 23N, R 10W, NMPM			
14. PERMIT NO. 15. ELEVATIONS (Show whether DF, ET, CE, etc.)		12. COUNTY OR PARISE	13. STATE		
14. PERSITA NO.		6674' KB	San Juan	NM	
16. Check Age		•	r Other Data		
Check Appropriate Box To Indicate Nature of Notice, Report, or Othe					
	()	WATER SHUT-OFF	REPAIRING V	WELL	
	ULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CA	1	
-	IANDON®	SHOOTING OR ACIDIZING	ABANDONME	X X	
REPAIR WELL	(Note: Report results			of multiple completion on Well	
(Other) Completion or Recompletion Report and Log form.) DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and sones per proposed.				e of starting any	
T.D. 4830' re Firished dri P.C.H. and conditioned'r Rigged up and LT&C and ST Cemented firs 225 sx 50-50 286 cu.ft.). casing OK whi held OK. Dro Circulated wi pumping 10 bk gel plus \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ached on 12-18-88 lling 7-7/8" hol ran IES & CDL nud. Laid down ran 127 jts. 4½' &C casing (T.E. t stage by pumpir pos + 2% gel (to Full mud returns le cementing. Bu opped opening bo th rig pump for 2 ols mud flush fol elloflake per sac celloflake/sk (t . Had full l mud flush and osed stage tool	logs by Welex drill pipe and OD, 11.6# & 10. 4825.32') set of 10 bbls mud flotal cement slurr while cementing mped plug with 1 mb. Opened stage hours. Cement lowed by 600 sx ck followed by 50 otal cement slur mud returns whapproximately 2 with 2500 psi - Nippled down BOP,	conditioned mu T.I.H. a drill collar 5#, J-55, 8 R 4 4830' RK lush followed y first stage g. Reciprocate 1000 psi - flow te tool @ 3649 ted 2nd stage 65-35 plus 1 0 sx 50-50 pos cry 2nd stage nile cementing bbls cement held OK. Jo set 4½" casin	d. nd s. d. B. by ed at '. by 2% + g. to ob	
8. I hereby certify that the foregoing is t	rue and correct			1 00	
SIGNED To Jacobs	TITLE G	englis (F	DATE 12-2		
(This space for Federal or State office	use)	TAN ACC	U D TUIL TO		
A BREATED BY	TITLE	DECS (~ 3	DATE		
APPROVED BY		OIL CC DIV	ARMINOTUR RESCUENCE AR	t'y	
	*See Instructions	3 1.	Smm.	and the second s	
			to any department or av	rency of the	

makes it a crime for any person knowingly and willfully to make to any department or agency of the