(November 1983) (Formerly 9-331)  DEPARTMENT OF THE INTERIOR verse side  BUREAU OF LAND MANAGEMENT	NM-36951
SUNDRY NOTICES AND REPORTS ON WELL!  (Do not use this form for proposals to drill or to deepen or plug back to a differe Use "APPLICATION FOR PERMIT—" for such proposals.)	$\mathbf{S}^{\mathrm{opt}}$
OIL XX CAB WELL OTHER  2. NAME OF OPERATOR	8. FARM OR LEASE NAME
DUGAN PRODUCTION CORP.  3. ADDRESS OF OPERATOR	Helsinki 9. WALL NO.
P.O. Box 420, Farmington, NM 87499  1. LOCATION OF WELL (Report location clearly and in accordance with the V State requirements)	nts. 52 10. FIELD AND POOL, OR WILDCAT
At surface AUG 0 3 1	RUEVEL UE AREA
2310' FSL & 2310' FWL OIL CON	Sec. 9, T23N, R10W, NMPM  12. COUNTY OR PARISH   13. STATE
14. PERMIT NO.   15. ELEVATIONS (Show whether DF, RT, GR. DIST. 6558 GL; 6570 KB	_ San Juan NM
16. Check Appropriate Box To Indicate Nature of Not	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
FRACTURE TREAT  SHOOT OR ACIDIZE  REPAIR WELL  TEST WATER SHUT-OFF  MULTIPLE COMPLETE  FRACTURE  SHOOTIN  CHANGE PLANS  (Other)	T.D., 4-1/2" Casing & cement X  ore: Report results of multiple completion on Well mpletion or Recompletion Report and Log form.)
T.D. 4610' reached on 7-22-89.  P.O.H. and run IES & CDL logs by Hall T.I.H. Conditioned mud. Laid down drill up and ran 110 jts. 4-1/2" OD, 10.5#, (T.E. 4629.03') set @ 4610' Cemented pumping 10 bbls mud flush followed by 22 1/4# celloflake per sack (total cement cu.ft.). Had full mud returns while Reciprocated casing OK while cementing 11:30 PM 7-22-89. Dropped opening bomb 3435'. Circulated 2-1/2 hours with rig by B.J. Titan by pumping 10 bbls mud flash + 12% gel and 1/4# celloflake per sace pos + 2% gel and 1/4# celloflake/sk (tote 1121 cu.ft.). Total cement slurry bot returns while cementing. Circulated all contaminated cement. Closed tool with complete @ 3:00 A.M. 7-23-89. Nippled of slips, cut off 4-1/2" casing. Released	J-55, 8 Rd, ST&C casing  1st stage by B.J. Titan by  5 sx 50-50 pos + 2% gel and  slurry first stage = 286  e cementing first stage.  First stage complete @  Opened two stage tool @  pump. Cemented 2nd stage  ush followed by 450 sx 65-  k followed by 100 sx 50-50  al cement slurry 2nd stage  h stages = 1407 cu.ft. Full  I mud flush plus trace of  2500 psi. Held OK. Job  Hown BOP. set 4-1/2" casing
18. I hereby certify that the foregoing is true and correct  SIGNED	ot
(This space for Federal or State office use)	ACCEPTED FOR RECORD
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	JUL 3 1 1989
	FARMINGTON RESOURCE ARE