

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO

NM-32124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Calgary

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

South Bisti Gallup Ext.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6, T23N, R10W, NMPM

12. COUNTY OR PARISH 13. STATE

San Juan NM

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

DUGAN PRODUCTION CORP.

3. ADDRESS OF OPERATOR

P.O. Box 420, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1980' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6573' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in & rigged up Four Corners Drilling Company rig #5. Spudded a 12-1/4" hole @ 11:15 AM 7-23-89. Drilled to 230'. Ran 5 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 210.67') set @ 222' RKB. Cemented with 135 sx class "B" + 2% CaCl₂ (total cement slurry = 159 cu.ft.). P.O.B. @ 3:00 PM 7-23-89. Circulated approx. 3 bbls cement to surface. Pressure tested surface casing & BOP 600 psi for 30 minutes before drilling out.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jim L. Jacobs

TITLE

Geologist

DATE

7-24-89

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

JUL 27 1989

FARMINGTON RESOURCE AREA

*See Instructions on Reverse Side

BY KIL