

Form 3160-5
(June 1990)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

5. Lease Designation and Serial No.

NM-50999

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

The Bear #2

9. API Well No.

30-045-28552

10. Field and Pool, or Exploratory Area

Wildcat Gallup

11. County or Parish, State

San Juan County, NM

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL
Sec. 34, T23N, R8W, NMPM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent☒ Subsequent Report☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment☐ Recompletion☐ Plugging Back☐ Casing Repair☐ Altering Casing☒ Other Spud & Surface Csg.☐ Change of Plans☐ New Construction☐ Non-Routine Fracturing☐ Water Shut-Off☐ Conversion to Injection☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in & rigged up Four Corners Drilling Company Rig #4. Spudded a 12-1/4" hole at 4:15 PM 3-30-92. Drilled to 230'. Ran 5 jts. 8-5/8", 24#, 8 Rd, ST&C casing (T.E. 211.67') set at 223'. Cemented with 135 sx class "B" + 2% CaCl₂ (total cement slurry = 159 cu.ft.). P.O.B. at 8:30 PM 3-30-92. Circulated 2 bbls cement to surface. W.O.C. 8 hours. Nippled up BOP and tested casing and BOP 1000 psi for 30 minutes - held OK.

ACCEPTED FOR RECORD

APR 02 1992

FARMINGTON RESOURCE AREA

BY

14. I hereby certify that the foregoing is true and correct

Signed

Jim L. Jacobs

Title Geologist

Date

3-31-92

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Title

NMOOD

Date