

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

Revised 12-1-55

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Pool Ballard Formation P.C. County Rio Arriba
Initial X Annual _____ Special _____ Date of Test 4/12/65
Company Sentinel Petroleum Corp Lease Jicarilla-Abel Well No. 3
Unit N Sec. 31 Twp. 24N Rge. 4W Purchaser _____
Casing 4-1/2 Wt. _____ I.D. _____ Set at 2574 Perf. 2479 To _____
Tubing _____ Wt. _____ I.D. _____ Set at _____ Perf. _____ To _____
Gas Pay: From _____ To _____ L _____ xG .650(E) -GL 1612 Bar.Press. 12
Producing Thru: Casing X Tubing _____ Type Well Single
Single-Bradenhead-G. G. or G.O. Dual
Date of Completion: _____ Packer _____ Reservoir Temp. _____

OBSERVED DATA

Tested Through (XXXX/Prover) (Choke) (XXXX/Meter) Type Taps _____

No.	Flow Data					Tubing Data		Casing Data		Duration of Flow Hr.
	(Prover) (Line) Size	(Choke) (Orifice) Size	Press. psig	Diff. h _w	Temp. °F.	Press. psig	Temp. °F.	Press. psig	Temp. °F.	
SI								<u>684</u>		<u>7 Days</u>
1.		<u>.750</u>						<u>480</u>	<u>67</u>	<u>3 Hrs</u>
2.										
3.										
4.										
5.										

FLOW CALCULATIONS

No.	Coefficient (24-Hour)	$\sqrt{h_{wpf}}$	Pressure psia	Flow Temp. Factor F _t	Gravity Factor F _g	Compress. Factor F _{pv}	Rate of Flow Q-MCFPD @ 15.025 psia
1.	<u>12.3650</u>		<u>492</u>	<u>.9933</u>	<u>.9608</u>	<u>1.047</u>	<u>6079</u>
2.							
3.							
4.							
5.							

PRESSURE CALCULATIONS

Gas Liquid Hydrocarbon Ratio _____ cf/bbl.
Gravity of Liquid Hydrocarbons _____ deg.
P_c _____ (1-e^{-s})


Specific Gravity Separator Gas _____
Specific Gravity Flowing Fluid _____
P_c 696 P_c² 484.416

No.	P _w P _t (psia)	P _t ²	F _c Q	(F _c Q) ²	(F _c Q) ² (1-e ^{-s})	P _w ²	P _c ² -P _w ²	Cal. P _w	P _w P _c
1.	<u>492</u>	<u>242.064</u>	<u>9.550</u>	<u>91.203</u>	<u>10.124</u>	<u>252.188</u>	<u>232.228</u>	<u>302</u>	
2.									
3.									
4.									
5.									

~~XXXXXXXXXXXX~~ CAOP 11,356 MCFPD; n .85

COMPANY SENTINEL PETR. CORP
ADDRESS _____
AGENT and TITLE Wayne B. Smith P.E.
WITNESSED HERMAN BAUER
COMPANY SENTINEL

REMARKS



INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_w).
MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
psia
- P_w = Static wellhead working pressure as determined at the end of flow period.
(Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- P_t = Flowing wellhead pressure (tubing if flowing through tubing, casing if
flowing through casing.) psia
- P_f = Meter pressure, psia.
- h_w = Differential meter pressure, inches water.
- F_g = Gravity correction factor.
- F_t = Flowing temperature correction factor.
- F_{pv} = Supercompressability factor.
- n = Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .