Sec. 34

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

and Offic	ce	Santa Fe
ease No.	SP.	079429
• •.		

Budget Bureau No. 42-R358.4.

Form Approved.

SUNDRY NOTICES AND REPORTS ON WELLS

GROUND The elevation of the development floor above sea level is 73	35 +	
The elevation of the transfer floor above sea level is 12	235 ft.	
DETAILS OF	WORK	
DETAILS OF		
DETAILS OF (State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import	and lengths of proposed casings; indicate mudding jobs,	cement-
(State names of and expected depths to objective sands; show sizes, weights,	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other important report of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand frand 33,600 gallons water. Maximum pressur	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054~3062 and seced 7-17-63, with 30,000# senter 1800. Minimum pressure 1300.	l
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other import To supplement report of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and seced 7-17-63, with 30,000* send to 1800. Minimum pressure 1300.	i I
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other imports of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35. Presently swaiting testing.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and seced 7-17-63, with 30,000# sand e 1800. Minimum pressure 1300.	i I
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other imports of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35. Presently swaiting testing.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and acced 7-17-63, with 30,000* sand a 1800. Minimum pressure 1300.	i !
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other imports of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand fr and 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35. Presently swaiting testing.	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and acced 7-17-63, with 30,000* send acced 7-17-63. With 30,000* send acced 1800. Minimum pressure 1300.	ed.
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other imports of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand frand 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35. Presently swaiting testing. I understand that this plan of work must receive approval in writing by Company Shar-Alan Oil Company Address 1402 Denver U. S. National Center	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and acced 7-17-63, with 30,000¢ sand acced 7-1800. Minimum pressure 1300. 1 ORIGINAL SIGNE RICHARS S. H.	BY
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other imports of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand frand 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35. Presently swaiting testing. I understand that this plan of work must receive approval in writing by Company Shar-Alan Oil Company	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and acced 7-17-63, with 30,000¢ sand acced 7-1800. Minimum pressure 1300. 1 ORIGINAL SIGNE RICHARS S. H.	BY
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other imports of 4-23-63, subject we 3079-3097 with 2 shots per ft. and sand frand 33,600 gallons water. Maximum pressur Injection rate 35.0 BPM. Rate on Frac 35. Presently swaiting testing. I understand that this plan of work must receive approval in writing by Company Shar-Alan Oil Company Address 1402 Denver U. S. National Center	and lengths of proposed casings; indicate mudding jobs, ant proposed work) 11 perforated from 3054-3062 and acced 7-17-63, with 30,000* send acced 7-17-63. With 30,000* send acced 1800. Minimum pressure 1300.	ed.