

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON Resuming (Other) Drilling operations	X

September 24, 1954, Ghost Ranch, Abiquin, New Mexico
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

James T. Watson

(Company or Operator)

Al Arthur E. Peak

(Lease)

Avis Drilling Company

(Contractor)


Well No. **1** in the **S W** $\frac{1}{4}$ **S E** $\frac{1}{4}$ of Sec. **35**T. **24 N**, R. **4 E**, NMPM., **None** Pool, **Rio Arriba** County.The Dates of this work were as follows: **September 7 to September 24, 1954**

Notice of intention to do the work (~~was~~) (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)

and approval of the proposed plan (~~was~~) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Cable tool operation was suspended at 2305'. Rotary rig was installed at that depth. 7" casing had previously been landed at 2256'. Flowing water was encountered between 2300' and 2320'. This water sand was shut off by a squeeze cement job, by Halliburton process, between 2225' and 2325', using 80 sacks and 300 lbs. pressure. Flowing water was found at 2360' to 2395'. This sand was also shut off by a squeeze cement job with plug set at 2201'. 300 sacks of cement were used and pressure was 3400 lbs. Drilling of plug is now in progress

Witnessed by **James T. Watson**
(Name)**James T. Watson**
(Company)**Operator**
(Title)

Approved:

OIL CONSERVATION COMMISSION

Eugene A. G. King
(Name)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name **James T. Watson**Position **Operator**Representing **James T. Watson**Address **Ghost Ranch, Abiquin, New Mexico**

oil & gas engineer - Dist. 3 SEP 20 1954
(Title) (Date)