Form 9-881 a (Feb. 1951)

\*\*\*

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	. Santa I	<b>7</b>
Lease No.	078915	
11-14	Lindrith	Uni

## SUNDRY NOTICES AND REPORTS ON WELLS

	1 100
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OF REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MARK	NATURE OF REPORT, NOTICE, OR OTHER GATA)
·	October 20th , 19 58
Well No. 26 is located 990 ft. from	
· · · · · · · · · · · · · · · · · · ·	(Range) (Meridian)
S. Blanco PC Ext. Rio	Arriba New Mexico
(Field) (County or	r Subdivision) (State or Territory)
DETAIL	LS OF WORK
OETAII (State names of and expected depths to objective sands; show size ing points, and all of	
(State names of and expected depths to objective sands; show size ing points, and all of the first objective sands; show size ing points, and all objective sands; show size ing points, and s	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenters important proposed work)  7 joints 3248; of 5-1/2" OD 15.5#  with 150 sacks coment.  howed top of coment at 2400.
(State names of and expected depths to objective sands; show size ing points, and all of the first of the sands; show size ing points, and all of the sands; show size in just just just just just just just just	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5% with 150 sacks coment.  howed top of coment at 2400'.  ng to 1000%. No pressure decrease
(State names of and expected depths to objective sands; show size ing points, and all of 6-7-58 TD 3259 REB. Set 7 J-55 casing at 3257 Temperature survey at 1 n one hour.	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5%  with 150 sacks coment.  howed top of cement at 2400'.  Ing to 1000%. No pressure decrease  writing by the Geological Survey before operations may be commenced.
(State names of and expected depths to objective sands; show size ing points, and all of 6-7-58 TD 3259 REB. Set 7 J-55 casing at 3257 Temperature survey at 1 n one hour.	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5%  with 150 sacks coment.  howed top of coment at 2400'.  Ing to 1000%. No pressure decrease  writing by the Geological Survey before operations may be commenced.
(State names of and expected depths to objective sands; show size ing points, and all of the first objective sands; show size ing points, and show size ing points,	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5%  with 150 sacks coment.  howed top of coment at 2400'.  Ing to 1000%. No pressure decrease  writing by the Geological Survey before operations may be commenced.
(State names of and expected depths to objective sands; show size ing points, and all of the first of the sands; show size ing points, and all of the sands of th	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5%  with 150 sacks coment.  howed top of cement at 2400'.  Ing to 1000%. No pressure decrease  writing by the Geological Survey before operations may be commenced.
(State names of and expected depths to objective sands; show size ing points, and all of the first objective sands; show size ing points, and show size ing points,	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5%  with 150 sacks coment.  howed top of cement at 2400'.  Ing to 1000%. No pressure decrease  writing by the Geological Survey before operations may be commenced.
(State names of and expected depths to objective sands; show size ing points, and all of the first of the sands; show size ing points, and all of the sands of th	LS OF WORK  se, weights, and lengths of proposed casings; indicate mudding jobs, commenter important proposed work)  7 joints 3248' of 5-1/2" OD 15.5#  with 150 sacks coment.  howed top of coment at 2400'.  ng to 1000#. No pressure decrease  writing by the Geological Survey before operations may be commenced.