MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

	Begin			_Fo	rmation_	Dake	ta	 	_County	Rto Ar	ribe	
nit	ial_	A	.nnual_			Spec	ial		_Date of '	Te st_	7-16-63	
mţ	any bhi l	011 Cem	pany		L	ease J	icarilla	Otere	Wel	l No.	32-28	
it	. <u> </u>	c. 28	_Twp	24N	Rge	. 51	Purc	haser	Page Nat	ural G	na Co.	
	ng 4 Wt											
bi	ng 2 3/8 Wt		I.D.		Set	at 654	Pe:	rf		To		
S	Pay: From_	T	·o		L	x	G 600 •	:: _GL]	Bar.Pr	ess. 12.0	
oc	lucing Thru:	Casin	g		Tub	ing	1	Type We	ell _s	ngle		
t∈	of Completi	.on: 7_	5-63		Packer	No.	Sin	gle-Brade _Reservo	enhead-G. (oir Temp.	G. or	G.O. Dual	
					•		ED DATA		-			
st	ed Through	(Prover	(Chol	<u>(e)</u>	(Meter)				Type Tap	s		
_		Flo	w Data				Tubing	Data	Casing Da	ata	T	
۰	(Prover) (Line)	(Orific	e)		Į				i	ļ		
+		Size		sig	h _w			°F.	 	Jr. •	Hr.	
T	2*	<u> </u>		82			87	74	1568 476		3 hre	
				-				•			7-0	
											 	
Ţ								1	L	<u> </u>	<u> </u>	
-r	066:-:-		<u>.</u>	+			CULATION		10		Det - C El	
				essure Flow Temp. Factor			Factor Fact					
	(24-Hour) $\sqrt{h_{w}}$		h _w p _f	p _f psia		Ft		Fg	Fp v		@ 15.025 psia	
╀	12.3650			 9	99	-9868		1.000	_	1.007	1.216	
+				<u> </u>								
				 -	PRE	SSURE C	ALCU ATI	ons	 			
I	iquid Hydrod	arbon R	atio			cf/bbl.		Speci	fic Gravi	ty Sep	arator Gas	
,,	ty of Liquid	-		-s \		deg.		•			wing Fluid_	
			(1-e	<u> </u>				°c	1036	_ ^P c	4145.3	
		P _t .	E O		(F 0)2	/5	0)2	ר ת	$P_c^2 - P_w^2$		2] D	
_ T	$P_{\mathbf{w}}$	r ₊ .	F _c Q		(F _c Q) ²	(1	c ^Q) ² -e ^{-s})	P _w 2	rc-rw		$\begin{array}{c c} al. & P_{\underline{W}} \\ P_{\underline{W}} & P_{\underline{C}} \end{array}$	
1	P _w		<u></u>					238.1	3.907.2			
- Т				-		-						
	Pt (psia)											
	Pt (psia)											
	Pt (psia)					MC PDD -					1.75 s 0.045	
SC MF	Pt (psia) 483 Plute Potenti	ial: 1.2		Comp	eny. Inc		n				1.75 1.0453	
SC MIF	Pt (psia)	ial: 1.2	1 011				n7	5			1.75 \$1.0453	
so MIF	Pt (psia) 483 Plute Potenti	ial: 1.2	1 011				n7	5			1.75 \$1.0453	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P_W) . MCF/da. @ 15.025 psia and 60° F.
- P_c 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- FgI Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.
- Note: If P_W cannot be taken because of manner of completion or condition of well, then P_W must be calculated by adding the pressure drop due to friction within the flow string to P_+ .