

o "C" #1	T
Sec. #26	24
	N

ACTIVE DISTRICT (SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office **Jicarilla Apache**
Tribal #13; Treat #21
Lease No. _____
Unit **Jicarilla Apache "C"**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	REPORT ON SAND-OIL FLOC & TESTING	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 15, 1955

Well No. **1** is located **990** ft. from **[N]** line and **990** ft. from **[W]** line of sec. **26**
C-55 NW 1/4 Sec. #26 **24-N** **5-W** **N.M.P.**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat **Hio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6658** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4620
4471 T.D. **4248** P.B.D.

Rigged up Lane Wells & set Baker magnesium bridge plug at 4360', 4-8-55. Dumped 2 sacks of cement on top of plug, top of cement at 4348'. Perforated 6-5/8" OD casing from 4285' to 4312' w/total of 108 bullet shots. Ran 2-3/8" OD BUE tubing set at 4270', 4-8-55. Sand oiled 6-5/8" OD casing perforations from 4285' to 4312' w/10,000 gal. #2 diesel fuel oil & 6,000# sand. Connected flow line and attempted to kick well off with input gas. Well blew dry, no shows of formation gas. Rigged up Halliburton, 4-9-55 and spotted 15 sacks of cement from 4329' to 4248'. Rig released @ 12:00 Noon, 4-9-55.

We intend to cap and temporarily abandon well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Amerada Petroleum Corporation**Address **Drawer D****Monument, New Mexico**By **R. C. Cappel**Title **District Superintendent**