

(SUBMIT IN TRIPLICATE)

Indian Agency Doles, New Mexico

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Jicarilla Apache
Allottee Cont. #11-Tr-#19
Lease No. J. Apache "B"

See-30	
T24N-R9W	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent report for setting 3 1/2" Casing</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 18, 1963

Well No. 12 is located 1175' ft. from N line and 1175' ft. from E line of sec. 30

NE/NE-See-30
(1/4 Sec. and Sec. No.)

T24N
(Twp.)

R9W
(Range)

MEPH
(Meridian)

Basin Dakota
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6626' ft. L/S Elev.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mud weights, cementing points, and all other important proposed work)

3-15-63 - 6725' Total Depth:

Set 3 1/2" OD 9.20#, J55, R2, SS Casing at 6721'; W/Horse Shoe on bottom, and Horse float collar at 6688', W/Bate Scratchers & Cent. (6690'-6484'); with D. V. Staging Tool in string at 2365'; Cemented by Halliburton, lower stage W/250 sacks 50/50 Permox out. W/12 1/2# Gilsomite per sack, mixed 4% Gel and 3/4% CPR2, and 100 Sack 50/50 Perm. 2% Gel and 3/4% CPR2, Max. Press. 600#, pumped plug to 6688' W/2000# at 1:15 PM, W/4000# Press. Csg. Hydro-tested in hole W/4000# while running. WOC, Lower stage, and ran B&B temp. survey, found cement outside of 3 1/2" Csg. at 5400'. Cemented second stage by Hallib. through D. V. Tool at 2365' W/75 Sax Reg. Out. mix 6% gel, (to cover P-C Zone) Max. P. 500#, Pump plug to 2365' at 5:45 PM, W/2500# Press. Ran B&B Temp. survey, found top of cement outside 3 1/2" Casing at 1965' on second stage.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

247-5353

By L.A. Pettyjohn

Title District Field Clerk

