(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
Allottee Magnolia
Contract - 12

SUNDRY NO	TICES AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	
NOTICE OF INTENTION TO TEST WATER SHUT	
NOTICE OF INTENTION TO REDRILL OR REPA	
NOTICE OF INTENTION TO SHOOT OR ACIDIZ	
NOTICE OF INTENTION TO PULL OR ALTER C	
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOV	E BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	December 8 , 19 55
	990 ft. from line and 1650 ft. from line of sec. 28
ell No is located	Tt. from Mine of sec.
Na 2 - 28	24-N 5-W NMPM
(14 Sec. and Sec. No.)	(Twp.) (Range) (Meridian)
licerilla Apache	Rio Arriba New Mexico
(Field)	(County or Subdivision) (State or Territory)
	DETAILS OF WORK
	ctive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work)
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi] 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to	Cotober 29, 1955
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gsli then back to 823 to	ctive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) October 29, 1955 November 22, 1955 :November 22, 1955 pipe 8 5/8 in. With 90 sacks cement set pe with 100 sacks cement, set 2283 48 ft. berger log 2340 T.D. Perforations - 16 shots ts from 2262 - 2270. 32 shots from 2274 - 232 o 2306. 48 shots from 2326 - 2338. lons water and 15000 lbs. sand broke at 1800 900 lbs. injection rate 22 barrels minute.
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi 1 in. tubing Sehlum 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gsl; then back to 823 to	Cotober 29, 1955 November 22, 1955 November 22, 1955 pipe 8 5/8 in. with 90 sucks cement set pe with 100 sucks cement, set 2283 48 ft. berger log 2340 T.D. Perforations - 16 shots ts from 2262 - 2270. 32 shots from 2274 - 238. lons water and 15000 lbs. sand broke at 1800
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi] 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gall then back to 823 to	ctive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) October 29, 1955 November 22, 1955 Pipe 8 5/8 in. With 90 sacks cement set pe with 100 sacks cement, set 2283 48 ft. berger log 2340 T.D. Perforations - 16 shots ts from 2262 - 2270. 32 shots from 2274 - 282 to 2306. 48 shots from 2326 - 2338. Lons water and 15000 lbs. sand broke at 1800 good lbs. in section rate 22 berrels minutes.
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi] 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gall then back to 823 to Tunderstand that this plan of work must Company Mike Abraham	Citive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) October 29, 1955 November 22, 1955 November 22, 1955 pipe 8 5/8 in. With 90 sucks cement set pe with 100 sacks cement, set 2283 48 ft. berger log 2340 T.D. Perforations - 16 shots to from 2262 - 2270. 32 shots from 2274 - 238 to 2306. 48 shots from 2326 - 2338. Lons water and 15000 lbs. sand broke et 1800 good lbs. in ection rate 22 berrels minute. Le receive approval in writing by the Geological Survey before operations may be definite expected.
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi] 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gall then back to 823 to Tunderstand that this plan of work must Company Mike Abraham	Citive sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) October 29, 1955 November 22, 1955 November 22, 1955 pipe 8 5/8 in. With 90 sucks cement set pe with 100 sacks cement, set 2283 48 ft. berger log 2340 T.D. Perforations - 16 shots to from 2262 - 2270. 32 shots from 2274 - 238 to 2306. 48 shots from 2326 - 2338. Lons water and 15000 lbs. sand broke et 1800 good lbs. in ection rate 22 berrels minute. Le receive approval in writing by the Geological Survey before operations may be definite expected.
Drilling commenced: Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gall then back to 823 to	City earnes; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) October 29, 1955 Nove for 3, 1955 November 22, 1955 pipe 8 5/8 in. With 90 sacks cement set pe with 100 sacks cement, set 2263 48 ft. berger log 2340 T.D. Perforations - 16 shots ts from 2262 - 2270. 32 shots from 2274 - 282 o 2306. 48 shots from 2326 - 2338. lons water and 15000 lbs. sand broke at 1800 good lbs. in section rate 22 barrels minutes. t receive approval in writing by the Geological Survey before operations may be dominanced. Ol. 134.60% DIST. 3
Completed: Tested and completed: Set 97 ft. surface 2341.59 in ft. 5½ pi 1 in. tubing Sehlumi 2256 - 260. 32 sion 88 shots from 2284 to Fract with 20000 gell then back to 823 to Iunderstand that this plan of work must Company Mike Abraham Address 918 Simms Bland	City earnes; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) October 29, 1955 Nove for 3, 1955 November 22, 1955 pipe 8 5/8 in. With 90 sacks cement set pe with 100 sacks cement, set 2263 48 ft. berger log 2340 T.D. Perforations - 16 shots ts from 2262 - 2270. 32 shots from 2274 - 282 o 2306. 48 shots from 2326 - 2338. lons water and 15000 lbs. sand broke at 1800 good lbs. in section rate 22 barrels minutes. t receive approval in writing by the Geological Survey before operations may be dominanced. Ol. 134.60% DIST. 3