

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Julce, New Mexico
Jicarilla Apache
Allotted Cont. #11-Tract #19
Lease No. J. Apache "B"

Sec-29
124N-R5W

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		Subsequent Report for setting 3 1/2" Casing	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 5, 1963

Well No. 13 is located 1000' ft. from N line and 1000' ft. from E line of sec. 29

SW/NE/NE-Sec-29
(34 Sec. and Sec. No.)

24N
(Twp.)

SW
(Range)

N14PM
(Meridian)

Basin Dakota
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

RECEIVED

APR 9 1963

The elevation of the derrick floor above sea level is 6707' ft.

DETAILS OF WORK

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate shuttings, cementing points, and all other important proposed work)

3-30-63 - 6838' Total Depth:

Set 3 1/2" OD 9.2#, 10RT, J55, R2, Youngstown, SS Casing, New, SET @ 6815' w/Howco Shoe on bottom, and Float Collar at 6783', w/Roto Scratchers and Centralizers on casing thru Dakota, Graneros and Pictured Cliffs Zones, w/D. V. Staging tool in string at 2446'; Cased. by Hallib. w/250 Sacks 50/50 Fomix Cmt. mixed 4% Gel & 3/4% CFR2, w/12 1/2# Fine grind Gileonite per sack, and 100 Sacks 50/50 Fomix Cmt. Mix 2% Gel & 3/4% CFR2, Max. Press. 1500#, Plug down at 6AM, w/2500#. Hydro-Tested 3 1/2" Cag. w/4500# while running. WOC - Ran B&R Temp. Survey, Cmt. outside 3 1/2" Cag. Lower stage at 5380' Hallib. Cmted. 2nd. stage through D. V. Tool at 2446' w/75 Sacks Class "C" Cmt, 6% Gel. Pumped plug to 2446' w/1000# Press. Closed tool and pressured up to 3000# Held OK. WOC - Ran B&R Temp. survey, Cmt. outside 3 1/2" Cag. Upper stage at 1900'. 4-2-63 - Drilled out D. V. Tool @ 2446' and drilled cement out of casing to 6783' DOD, and Test 3 1/2" Casing w/4500# Press. for 1-Hr. Held OK.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be started.

Company Amerada Petroleum Corporation

Address Box 1469

Durango, Colorado

247-5353

By [Signature]

Title Production Foreman

