Budget Bureau No. 42-R358.4. Approval expires 12-31-60.

Form 9-881 a (Feb. 1951)

٠.				_
ſ	`			X
		,	27	
I				

Albuquerque, New Mexico

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Offic	·•	Santa	To.
Lease No.	<b>3</b> 7	07856	2
Unit	<b>-</b> -	*****	

NOTICE OF INTEN	TION TO DRILL		SUBSEQUE	IT REPORT OF WATE	R SHUT-OFF	1111 1
NOTICE OF INTEN	TION TO CHANGE PLANS	s	SUBSEQUE	IT REPORT OF SHOO	TING OR ACIDIZING	\$ 75 t s
NOTICE OF INTEN	ITION TO TEST WATER S	SHUT-OFF	SUBSEQUE	IT REPORT OF ALTE	RING CASING	
NOTICE OF INTEN	TION TO RE-DRILL OR	REPAIR WELL	SUBSEQUE	IT REPORT OF RE-DI	ILLING OR REPAIR	C. C. OLUGI VIII
NOTICE OF INTEN	ITION TO SHOOT OR AC	IDIZE	SUBSEQUE	IT REPORT OF ABAN	DONMENT	
NOTICE OF INTEN	TION TO PULL OR ALTE	ER CASING	SUPPLEME	ITARY WELL HISTOR	Y	X_
NOTICE OF INTEN	ITION TO ABANDON WEL	<b>L</b>				
	(INDICATE A	BOVE BY CHECK MAR	RK NATURE OF REPO	RT, NOTICE, OR OTHI	<b>,</b>	
T.ofts	rook		***************************************		Nay 2	9 , 19 <b>6</b> 2
Vell No. 7-		790 ft. from	[N] ::	nd 790 ft. f	[Ε] <sub>1</sub> .	. 27
/ en 140	is located	iii. It. Iroi	m-XX line ar	iait. i	rom	or sec
ne ne	27	24n	7 <b>%</b>	MPM		
(% Sec. and Escrito	•	(Twp.) Rio Arr	(Range)	(Meridian)		_
(Fiel			y or Subdivision)		(State or Territory	
he elevation	of the derrick flo			ft.		
		DETA	AILS OF WO	KK.		
	expected depths to obj	ing points, and all	other important p	roposed work)		
Perf. Gal 11,990 ga Final pre	lup from 57 is. gelled ssure 2800 set at 5736	'10' to 57' oil. BD psi, shut-	34' w/4 s 3500 psi, -in 1400	PF. SOF ( Avg. T.P. psi, Avg.	e/40,000# . 2600 pe	sand & i, BPM.
Perf. Gal 41,990 ga Pinal pre PE 5726'	lup from 57 ls. gelled ssure 2800 set at 5736	ing points, and all /10' to 57: oil. BD: pei, shut- i'. Put w	34' w/4 s 3500 psi, -in 1400 wll on pu	PF. SOF AVG. T.P.	2600 pe I.R. 27 Ing load	sand 6 i, BPM. oil.
Perf. Gal 1,990 ga Pinal pre PB 5726'	lup from 57 is. gelled ssure 2800 set at 5736	ing points, and all  10° to 57; oil. BD; psi, shut- i'. Put w	34' w/4 8 3500 psi, -in 1400 wll on pu	PF. SOF AVG. T.P.	2600 pe I.R. 27 Ing load	sand 6 i, BPM. oil.
Perf. Gal 11,990 ga Pinal pre PE 5726'	lup from 57 ls. gelled ssure 2800	ing points, and all  10° to 57; oil. BD; psi, shut- i'. Put w	34' w/4 8 3500 psi, -in 1400 wll on pu	PF. SOF AVG. T.P.	2600 pe I.R. 27 Ing load	sand & i, BPM.
Perf. Gal 1,990 ga Inal pre 72 5726	lup from 57 1s. gelled ssure 2800 set at 5736  At this plan of work mu 1 R. Reese	ing points, and all  10° to 57; oil. BD; psi, shut- i'. Put w	34' w/4 8 3500 psi, -in 1400 ell on pu	PF. SOF AVG. T.P.	2600 pe I.R. 27 Ing load	sand & i, BPM.

By MORRIS B. JONE Storris B. Jones
Title

GPO 862040