

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SP-078562

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Lybrook

9. WELL NO.

7-20

10. FIELD AND POOL, OR WILDCAT

Escrito Gallup

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

27-24N-7W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6939 DF

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT XXX

ALTERING CASING

SHOOTING OR ACIDIZING XXX

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Get retrievable bridge plug at at 5650'.

Perforated as follows:

INTERVAL	Shots Per Ft.	Shots Fired
5585-88	2	6
5594.5	1	1
5600	1	1
5605.5	1	1
5610	1	1
5614	1	1

Sand water fracked after pumping 1500 gallons 28% acid with 15,000#'s
20-40 sand and 14,400 gallons water. Breakdown 2400, max. 2400 avg 2200.

Removed bridge plug.

Put well back into production.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry R. Bugh

TITLE

Vice President

DATE

4-12-71

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side