SUNDRY NOTICES AND REPORTS ON WELLS  Control of the part of the pa	TOTAL SENERT NAME
2. NAME OF OPERATOR  1. E. T. Enddirmsland  3. ADDRESS OF OPERATOR  4. COATION OF WELL (REPORT LOCATION CLEARLY, See space 17 below.)  AT SURFACE: 1850' FNL & 790' FEL AT TOP PROD INTERVAL: Same	8 FARM CHIERDER AME Subject 9. WELL NO  10. FIELD OF WILLIAM NAME South Blanco F  11. SEC. T. R. M. OT ELF AND SUBJECT AREA 26-24N-1W  12. COUNTY OR FARISH 13. STATE
AT TOTAL DEPTH: Same  AT TOTAL DEPTH: Same  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO  15. ELEVATIONS (SHOW DF, KDE AND
REQUEST FOR APPROVAL TO:  SUBSEQUENT REPORT OF:  TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*  (other)  SUBSEQUENT REPORT OF:  SUBSEQUENT REPORT OF:  SUBSEQUENT REPORT OF:  SUBSEQUENT REPORT OF:  U. S. GEOLOGICA FARMINGTON	U.S. GEOLOGICA, SUPPLY ON AND GAS GREEN TO TOUR PROPERTY OF Form 9-310.) 1 0 150.
measured and true vertical depths for all markers and zones pertinents  See attached modifications  This well has been previously approved for requesting approval of the following abandonment	plugging. We are herein t procedure.
Do not pull any of the 4½" casing leaving t Cement with 270 sacks of Class B neat from top t	to bottom down the $4\frac{1}{2}$ " casing.
Do not pull any of the 4%" casing leaving t	to bottom down the $4\frac{1}{2}$ casing.
Do not pull any of the 4½" casing leaving to Cement with 270 sacks of Class B neat from top to Place a dry hole marker.  Please contact Dave Simmons at the following information is needed. Home: 505-327-2813	to bottom down the $4\frac{1}{2}$ casing. ng numbers if additional
Do not pull any of the 4½" casing leaving to Cement with 270 sacks of Class B neat from top to Place a dry hole marker.  Please contact Dave Simmons at the following information is needed. Home: 505-327-2813  Work: 505-326-2510  We propose to do this work by September 20.	to bottom down the $4\frac{1}{2}$ " casing.  In numbers if additional additional and the second s
Do not pull any of the 4½" casing leaving to Cement with 270 sacks of Class B neat from top to Place a dry hole marker.  Please contact Dave Simmons at the following information is needed. Home: 505-327-2813  Work: 505-326-2510	to bottom down the $4\frac{1}{2}$ " casing.  In numbers if additional additional and the second s

## U. S. GEOLOGICAL SURVEY Drawer 600 Farmington, New Mexico 87499-00600

Attachment to Notice of

Intention to Abandon

Re: Permanent Abandonment

Well: 6 Sunico Federal

## CONDITIONS OF APPROVAL

 Plugging operations authorized are subject to the attached "General Requirements for Permanent Abandonment of Wells on Federal Leases."

- The Farmington office (telephone (505) 325-4572) is to be notified in sufficient time for a representative to witness all plugging operations.
- 3. Blowout prevention equipment is required.
- 4. In addition to normal filling of pits and cleanup of location, additional surface restoration work may be required, i.e. ripping of pad and/or access road, reseeding, etc. We have asked the Bureau of Land Management for the surface restoration requirements for this well and we should be able to furnish you these requirements within 30 days. After plugging the well and before making final clean-up, you should contact this office unless you have already been advised as to what additional surface restoration work is required.
- 5. The following modifications to your plugging program are to be made (when applicable):
  - a) Spot cement in 4/2" casing with tubing from T.D. to surface.
  - b) Bradenhead Squeeze 858" X 42" annulus with cement to cover surface casing shoe from 150' to surface.

Office Hours: 7:30 A.M. to 4:15 P.M.