REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON*

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Form 9–331	Form Approved. Budget Bureau No. 42-R1424
Dec. 1973 UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SF 080715 6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
SUNDRY NOTICES AND REPORTS ON WELL (Do not use this form for proposals to drill or to deepen or plug back to a direservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 10V 1 5 1982 8. FARM OR LEASE NAME GRAND JUNCTION. CO
1. oil gas well other other	9. WELL NO. 6
2. NAME OF OPERATOR E. L. Fundingsland 3. ADDRESS OF OPERATOR P. O. Box 1157 Littleton, Colorado 80160 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1850' FNL & 790' FEL AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	10. FIELD OR WILDCAT NAME South Blanco, PC 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	Sec. 20 T24N RIW 12. COUNTY OR PARISH 13. STATE Rio Arriba New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF N REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT TEST WATER SHUT-OFF FRACTURE TREAT	OFEN 7540 Ground
SHOOT OR ACIDIZE	(NOTSUFJEPORT results of multiple tompletion or zone

N. Change on Form 9-330.)

(other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertirent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Oct. 15, 1982-Rigged up service rig, picked up 2 3/8" tubing and ran into hole. Tagged botton at 3449'. Pumped 14 barrels water to clear tubing. Spot cement with 300 sacks from 3449' to surface.

Tied on to bradenhead and squeezed 8 5/8"" x $4\frac{1}{2}$ " annulus with 35 sacks at 250 psi.

Pumped cement on top of casing and around well head and installed dry hole

Rigged down and moved off location.

Subsurface Safety Valve: Manu. and Type

y that the foregoing is true and correct 18. I hereby

TITLE Vice President DATE

11/11/82

(This space for Federal or State office use)

Set @

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: TITLE

Approved as to plugging of the well bore.

Liability under bond is retained until surface restoration is completed.

e Instructions on Reverse Side

M. MILLENBACH AREA MANAGER