

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR  
CONTINENTAL OIL COMPANY
3. ADDRESS OF OPERATOR  
P.O. Box 466, HALL, TEXAS 75820
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1849' FNL & 1849' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/> repair tie.	<input checked="" type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

5. LEASE  
Contract 36
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Sicario Apache
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Northeast Haynes
9. WELL NO.  
10
10. FIELD OR WILDCAT NAME  
Cotton Valley
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 21, T. 22N, R. 5W
12. COUNTY OR PARISH  
Harrison
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6680' Gd

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-24-79 MIRU, kill well. tried to isolate leak.  
perf @ 500' ; squeeze 200 ex class B cement  
give port to surf  
drill out cement. press test held ok. pull pkr.  
ran subb. eqpt.  
well must be swabbed constantly to produce.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Butler TITLE Admin. Supv. DATE 5-25-79

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

USGS Durango 5

File

BEA

\*See Instructions on Reverse Side