

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **SF 078663**
Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	X
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 12, 1960

Byrd
Well No. **1-23** is located **990** ft. from **SX** line and **850** ft. from **WX** line of sec. **23**
NE NE/4 Sec. 23 **24N** **7W** **NMPM**
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Devils Fork **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the ~~bottom~~ **Ground** above sea level is **6732**.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job, casing points, and all other important proposed work)

TD 5684

Perforated Gallup formation from 5562-5600' with 2 SPF, SWF w/59,000 gallons water & 59,000# sand. TP 2700 psi, set BP at 5530'. Perf from 5444-5474' and 5386-5408' w/2 SPF. SWF w/40,000# 20-40 and 20,000# 10-20 sand. BD 1300 psi, TP 2600 PSI, IR 43.3 BPM. Final press. 1200 psi.

Ran 177 joints 2-3/8" tubing, TE 5580' set at 5590'.

SIFIP.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Val R. Reese & Associates, Inc.**

Address **Lobby of Simms Bldg.**
Albuquerque, New Mexico

By *Lewis L. Jameson*
Title **Geologist**