Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

| FORM APPROVED |
|-----------------------------|
| Budget Buresu No. 1004-0135 |
| Expires: March 31, 1993 |

5. Lease Designation and Serial No.

NMSF 078563 SUNDRY NOTICES AND REPORTS ON WELLS 5. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. NA Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE NA 1. Type of Weil ☑ Oil ☐ Gas Well ☐ Well 8. Weil Name and No. BYRD 1-2-5 2. Name of Operator UNIVERSAL RESOURCES CORPORATION 9. API Well No. 3. Address and Telephone No. 1331 17th Street, Suite 300, Denver, CO 80202 303-672-6970 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) DEVILS FORK GALLUP 11. County or Parish, State 990' FNL; 850' FEL; Section 23, T24N-R7W Rio Arriba, NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Change of Plans Recompletion New Construction Plugging Back Non-Routine Fracturing Casing Renair Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multi 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled. give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 2-15-96 Get final plugging procedures from Wayne Townsend (BLM) at 8:25 AM. Road rig to location. RU & NU BOP. TOOH with 2-3/8" tubing (3163'). RIH with 2-3/8" tubing. Tag up @ 3740. PU to 3732'. Spot balanced plug 3500' to 3732' (24 sx). PU to 3354' & reverse circulate. Stand back 4 jts. Tag plug @ 3479'. PU to 2132'. Pressure test casing to 600 psi (OK). Spot 2-16-96 24 sx balanced plug 1867' to 2132'. POOH. Perforate 4 holes @ 1661'. Could not pump into perfs. RIH to 1711'. Spot 29 sx balanced plug 1711' to 1383'. PU to 275'. Mix and pump 30 sx cement. Good returns @ surface. WOC. Tie on to bradenhead could not pump. Cut off wellhead. Cement down on 4-1/2"-8-5/8" annulus. Top off with 25 sx cement. Rig down and prepare to move to 2-21-96 Cut rig anchors and installed dry hole marker. 14. I hereby certify that the foregoing is true and correct OPERATIONS SUPERINTENDENT Signed (This space for Federal or State office use) Approved by Conditions of approval, if any: HA VOR HEL

*See instruction on Reverse Side .

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statement

or representations as to any matter within its jurisdiction