

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office NM
Lease No. 042835
Unit USA John S. Dashko

X		

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

John S. Dashko

Farmington, New Mexico December 5, 1963

Well No. 1 is located 530 ft. from NM line and 790 ft. from W line of sec. 15

SW/4 SW/4 Section 15 T-24N R-7W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Esquite Gallup Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7090 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

As a result of the above well's production declining to uneconomic rates, we plan to plug and abandon the John S. Dashko No. 1 as follows:

1. Spot 30 sacks cement 6073 (PBD) to 5880 (Perfs 5936-6015) and squeeze.
2. Run free point, cut off 5-1/2" casing as deep as possible, and pull casing.
3. Spot 40 sacks cement 50' in top of 5-1/2" casing stub to 50' above.
4. Spot 50 sacks cement 3150-3250 (top of Mesaverde 3205') unless top of 5-1/2" casing stub is above this depth.
5. Spot 50 sacks cement 2460-2550 (Pictured Cliffs 2460-95).
- 6.. Spot 50 sacks cement 350-450 in base of surface pipe.
7. Spot 10 sacks cement 0-25'.
8. Erect abandonment marker and clean up location.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address P. O. Box 480

Fred L. Nabors, District Engineer

Farmington, New Mexico

By ORIGINAL SIGNED BY
F. L. NABORS

Above procedure verbally approved December 5, 1963
Baier to Hollingsworth.

Title _____