

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil
Well☒ Gas
Well☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FSL & 990' FWL

Sec. 13, T24N, R5W

5. Lease Designation and Serial No.

Contract 37-A

6. If Indian, Allotted or Tribe Name

Jicarilla Apache

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Sunset #1

9. API Well No.

30 039 05434

10. Field and Pool, or Exploratory Area

Ballard Pictured Cliffs

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

- ☒ Notice of Intent
- ☐ Subsequent Report
- ☐ Final Abandonment Notice

- ☒ Abandonment
- ☐ Recompletion
- ☐ Plugging Back
- ☐ Casing Repair
- ☐ Altering Casing
- ☐ Other

- ☐ Change of Plans
- ☐ New Construction
- ☐ Non-Routine Fracturing
- ☐ Water Shut-Off
- ☐ Conversion to Injection
- ☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plan to plug well as follows:

1. Set cast iron bridge plug at 2390' (top Pictured Cliffs perforation is at 2410').
2. Spot Class B cement inside casing from 2390' to 1782' to cover Pictured Cliffs top at 2408' and Ojo Alamo top at 1882'.
3. Pump cement between 8-5/8" surface casing and 5-1/2" production casing to cover 50' below surface casing shoe at 104'.
4. Spot cement inside production casing from 154' (50' below surface casing) to surface.
5. Cut off casing heads and install dry hole marker.

Job to be completed by August 31, 1999.

14. I hereby certify that the foregoing is true and correct

Signed

John Alexander
John Alexander

Title

Vice-president

Date

6/9/99

(This space for Federal or State office use)

Approved by

[Signature]

Title

Petroleum Engineer

Date

8/20/99

Conditions of approval, if any:

Nacimiento top needs to be covered. Inside/outside
Nacimiento top @ 1384'. Surface Restoration Attached

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side