

Form 3-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIORSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

GEOLOGICAL SURVEY

NM-03595

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME None	
2. NAME OF OPERATOR Bco, Inc.		8. FARM OR LEASE NAME Judy	
3. ADDRESS OF OPERATOR P.O. Box 669, Santa Fe, N.M. 87501		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO. 790 FEL 790 ES L Sec 17 T24N R7W NMPM		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 17-24N-7W NMPM	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 7305		12. COUNTY OR PARISH Rio Arriba	
		13. STATE NM	



16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

NOTE This well was formerly called the Escrito Gallup Unit #14.

11-20-72 Set E-Z drill packer at 5900'. Squeezed existing perforations, (6110-40), with 100 sacks Class "A" cement. Perforated at 5200' with 4 shots. Set E-Z drill packer at 5160' and cemented casing with 150 sacks Class "C", 4%gel, cement.

11-24-72 Ran cement quality log and compensated neutron log.

12-4-72 Perforated with two shots per foot 5093-5095; 5075-5077; 5062-5064; 5051-5055; and 5032-5036.

12-5-72 Spotted 500 gallons 15% acid. Sand water fracked with 17,500 #'s 20-40 sand and 18,510 gallons water.

12-20-72 Placed on pump jack. Produced about 50 barrels of water a day with a slight oil cut that was too small to measure.

Attachments:

USGS - Two copies of each log run. One copy of Halliburton cement and frac reports.

OCC - One copy of each log run. One copy of Halliburton cement and frac reports.

Original Signed by

LEON B. HARTMAN

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

President

APR 25 1973

DATE 4-24-73

(This space for Federal or State office use)

APPROVED BY

TITLE

OIL CON. COM.
DIST. 3

DATE

CONDITIONS OF APPROVAL, IF ANY: