

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-03595

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Non-Commercial well.

2. NAME OF OPERATOR

Bco, Inc.

3. ADDRESS OF OPERATOR

P.O. Box 669, Santa Fe, N.M. 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

790 FEL and 790 FSL Sec 17 T24N R7W NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

GR 7305

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Judy

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

17-24N-7W NMPM

12. COUNTY OR PARISH 13. STATE

Rio Arriba

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☒

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☒
☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-30-73 Set E-Z drill at 4950' and squeezed existing perforations, (5032-5093), with 50 sacks Class A cement. Perforated 3728-3729 with two HJ 4" shots. Tried to squeeze but couldn't. Set E-Z drill at 3707'. Perforated 3460-3461 with two HJ 4" shots. Squeezed 3460 to 3707 with 150 sacks Class A cement.

5- 3-73 Ran cement bond log, determined cement was inadequate.

5- 4-73 Perforated with two HJ 3 3/8" shots. 3592-3593

5-16-73 Set E-Z drill at 3406' and squeezed with 150 sacks Class A cement.

5-18-73 Ran cement bond log. Perforated 3589-3596 with 2 HJ 4" shots per foot.

5-19-73 Set RTTS at 3525 and swabbed well. Treated formation with 2,000 gallons 15% acid. Swabbed. Treated formation with 50 gallons Pro Tex for scale. Pulled RTTS, re-ran tubing and swabbed. Slight show of gas produced with water.

5-20-73 Well temporarily abandoned.

ATTACHMENTS

Copies of Halliburton squeeze reports.

Two copies to USGS and one copy to OCC of CBL run 5-18-73

Two copies to USGS and one copy to OCC of CBL run 5-3-73 previously sent by cover letter dated 5-14-73.

18. I hereby certify that the foregoing is true and correct

SIGNED

Harry R. Bigh

TITLE

President

DATE

7-10-73

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: