

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐  
2. NAME OF OPERATOR  
Merrion Oil & Gas Corporation  
3. ADDRESS OF OPERATOR  
P. O. Box 1017, Farmington, New Mexico 87499  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650' FSL and 835' FEL  
AT TOP PROD. INTERVAL: Same  
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
SF 078886  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Canyon Largo Unit  
9. WELL NO.  
124  
10. FIELD OR WILDCAT NAME  
Devils Fork Gallup  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 17, T24N, R6W  
12. COUNTY OR PARISH  
Rio Arriba  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6606' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

BUREAU OF LAND MANAGEMENT  
FARMINGTON RESOURCE AREA

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-24-84  
Placed 25 sx (30 cu. ft.) Class B from 5589 - 5260' to cover Gallup Perfs.  
Placed 25 sx (30 cu. ft.) Class B from 4650 - 4320' to cover top of cement and Mesaverde Boundary.  
Perforated 2 holes @ 3680'.  
Placed 27 sx (32 cu. ft.) Class B inside and outside casing from 3680 - 3580.  
Placed 38 sx (45 cu. ft.) Class B from 2250 - 1750 to cover Lewis top, Pictured Cliff, Fruitland and 50' above cement top.  
Perforated 2 holes @ 1670'.  
Placed 62 sx (73 cu. ft.) inside and outside 1670 - 1440' to cover Ojo Alamo.  
Placed 25 sx (30 cu. ft.) Class B 250' - surface.  
Pumped 35 sx (41 cu. ft.) Class B down Bradenhead.  
Drilling mud between all plugs.  
Erected dry hole marker. 6-24-84

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED \_\_\_\_\_ TITLE Operations Manager DATE 6/27/84

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

NMOCC

\*See Instructions on Reverse Side