For (1	m 9-	-881 a 951)	•	

(SUBMIT IN TRIPLICATE)

Land Office Santa Fe Lesso No. NM=03595=A Unit Colean Federal

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

NOTICE OF INTENTION TO DRILL NOTICE OF INTENTION TO CHANGE		1 1	INT REPORT OF WATER SHI		
NOTICE OF INTENTION TO TEST WA			NT REPORT OF SHOOTING NT REPORT OF ALTERING		
NOTICE OF INTENTION TO RE-DRIL			NT REPORT OF RE-DRILLIN		
NOTICE OF INTENTION TO SHOOT	OR ACIDIZE	l II	NT REPORT OF ABANDONM		
NOTICE OF INTENTION TO PULL OF	R ALTER CASING	1 11	NTARY WELL HISTORY		h.,
NOTICE OF INTENTION TO ABANDO	N WELL	1 11		·	
(INDIC	CATE ABOVE BY CHECK MA	ARK NATURE OF REP	DRT, NOTICE, OR OTHER DA	TA)	
		•	·	April 22	, 19 .
ell No. 1 is loca	ated 1980 ft.fro	om } line a	nd 1980 ft from	E line of sec	
SE/4 of Sec. 17		()		inic or sec.	
(½ Sec. and Sec. No.)	24 N (Twp.)	(Range)	N.M.P.M. (Meridian)		
serito (Gallup)	Rio Arrib	4	Kasa	Mexico	
(Field)	(Coun	ty or Subdivision)	(St	ate or Territory)	
		AILS OF WO			
te names of and expected depths	to objective sands: show	sizes, weights, and	engths of proposed casing	er indicata muddina isl	ha
	ing points, and a	ll other important i	proposed work)	s; indicate mudding jo	bs, ceme
l spudded by Rutled	ing points, and a	ll other important :	proposed work)	•	bs, ceme
l spudded by Rutled ts of 8-5/8" O.D. 2	ing points, and a ge Drilling Con 44 JS5 surface	mpany on 4/ casing set	proposed work)	•	bs, ceme
l spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea	ing points, and a ge Drilling Co 4# JS5 surface surement on 4/	upany on 4/ casing set 20/60.	19/60. (@ 210 ft ro	tary	bs, ceme
l spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face easing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. canent and d satisfact	19/60. @ 210 ft ro	tary	bs, ceme
l spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face easing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. canent and d satisfact	19/60. @ 210 ft ro	tary	bs, ceme
l spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face easing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. cannet and d satisfact	19/60. @ 210 ft ro	tary	bs, ceme
spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face casing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. cannet and d satisfact	19/60. @ 210 ft ro	tary	be, ceme
spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face casing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. cannet and d satisfact	oroposed work) 19/60. @ 210 ft ro circulated are prily.	tary and casing.	be, ceme
l spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face easing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. cannet and d satisfact	oroposed work) 19/60. @ 210 ft ro circulated are prily.	tary and casing.	bs, ceme
l spudded by Rutled ts of 8-5/8" 0.D. 2 kelly bushing mea face easing set with face casing tested	ge Drilling Co 4# JS5 surface surement on 4/ h ##O sacks of to 1000# - held	upany on 4/ casing set 20/60. cannet and d satisfact	oroposed work) 19/60. @ 210 ft ro circulated are prily.	tary and casing.	be, ceme
l spudded by Rutled ts of 8-5/8" O.D. 20 kelly bushing mea face easing set with face casing tested to led out from under	ge Drilling Com 4# JS5 surface surement on 4/2 h ##0 sacks of to 1000# - help surface casing	mpany on 4/ casing set 20/60. cament and d satisfact g 12/21/60.	19/60. @ 210 ft ro circulated are orily.	PR 27 1960	be, ceme
l spudded by Rutled ts of 8-5/8" O.D. 20 kelly bushing mea face easing set with face casing tested to led out from under	ge Drilling Com 4# JS5 surface surement on 4/2 h ##0 sacks of to 1000# - help surface casing	mpany on 4/ casing set 20/60. cament and d satisfact g 12/21/60.	19/60. @ 210 ft ro circulated are orily.	PR 27 1960	be, ceme
l spudded by Rutled ts of 8-5/8" O.D. 2 kelly bushing measures easing set with face casing tested to led out from under	ge Drilling Con ## JS5 surface surement on 4/ h ##0 sacks of to 1000# - heli surface casing	mpany on 4/ casing set 20/60. cament and d satisfact g 12/21/60.	19/60. @ 210 ft ro circulated are orily.	PR 27 1960	he, ceme
face casing set with face casing tested of led out from under lunderstand that this plan of woompany Louis Dorfman	ge Drilling Con ## JS5 surface surement on 4/ h ##0 sacks of to 1000# - heli surface casing	mpany on 4/ casing set 20/60. casent and d satisfact g 12/21/60.	19/60. @ 210 ft ro circulated are orily.	PR 27 1960	he, ceme
l spudded by Rutled ts of 8-5/8" O.D. 20 kelly bushing measure casing set with face casing tested to led out from under lunderstand that this plan of wompany Louis Dorfman	ge Drilling Con 4# JS5 surface surement on 4/ h ##0 sacks of to 1000# - held surface casing ork must receive approval an ile Dallas Bui	mpany on 4/ casing set 20/60. casent and d satisfact g 12/21/60.	eirculated are prily.	prations may be comme	nenced.
l spudded by Rutled ts of 8-5/8" O.D. 20 kelly bushing measures casing set with face casing tested lied out from under lunderstand that this plan of woompany Louis Dorfm. 836 Mercant:	ge Drilling Con 4# JS5 surface surement on 4/ h ##0 sacks of to 1000# - held surface casing ork must receive approval an ile Dallas Bui	mpany on 4/ casing set 20/60. cament and d satisfact g 12/21/60.	19/60. @ 210 ft ro circulated are orily.	pand casing. PR 2.7 1960 Perations may be completed to show the complete to	nenced.