Form	9-831 a
(Feb	. 1951)

(SUBMIT IN TRIPLICATE) UNITED STATES

GEOLOGICAL SURVEY

DEPARTMENT OF THE INTERIOR

Land Office	sants Fe
	CO472-1
Lease No	nkin-Federal
Unit	

	SUBSEQUENT REPORT OF WATER SHUT-OFF
OTICE OF INTENTION TO DRILL	OF SUCOTING OR ACIDIZING
OTICE OF INTENTION TO CHANGE PLANS.	SUBSECUENT REPORT OF ALTERING CASING
OTICE OF INTENTION TO TEST WATER SHUT-OFF	DE DE DE DE LING OR REPAIR
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO PULL OR ALTER CASING	Water Frac.
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MA	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	July 14 , 1999
.160	(N) 1150 to from L line of sec.
/ell No. 1-4 is located 1460 ft. fro	om \mathbb{R} line and \mathbb{R} ft. from \mathbb{R} line of sec.
J. Con 17 24N	Jii
/4 Sec. 17 244 (W Sec. and Sec. No.) (Twp.)	(Range) (Meridian)
uth Blanco P. C. Ric	Arriba
(Cour	Ity of ounds mon)
	Walls OF WORK we sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work)
(State names of and expected depths to objective sands; showing points, and	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work)
(State names of and expected depths to objective sands; showing points, and	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) all other important proposed work) all other important proposed work) all other important proposed work indicate mudding jobs, cementall other important proposed work)
State names of and expected depths to objective sands; showing points, and .25-99 Total Depth 3103'. C.O.T.	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 w/32,000 gallons water and
(State names of and expected depths to objective sands; showing points, and .25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
(State names of and expected depths to objective sands; showing points, and -25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
(State names of and expected depths to objective sands; showing points, and 25-99 Total Depth 3103'. C.O.T.	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
(State names of and expected depths to objective sands; showing points, and -25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
(State names of and expected depths to objective sands; showing points, and -25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
(State names of and expected depths to objective sands; showing points, and -25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
(State names of and expected depths to objective sands; showing points, and -25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and .max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and .25-99 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and .max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and .25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. BD pr. 1800#	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,000 gallons water and max. pr. 1450%, avg. tr. pr. 1000%.
State names of and expected depths to objective sands; showing points, and .25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. RD pr. 1800# I.R. 31.2 BFM. Flush 3160 Drupped 2 sets of 10 balls	weights, and lengths of proposed casings; indicate mudding jobs, cementall other important proposed work) .D. 3090'. Water fractured Fictured Cliffs 42-56; 3070-76 v/32,800 gallons water and .max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and 25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000 sand. ED pr. 1800 I.R. 31.2 BHM. Flush 3160 Dropped 2 sets of 10 balls	weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and , max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and 25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000# sand. ED pr. 1800# I.R. 31.2 BHM. Flush 3160 Dropped 2 sets of 10 balls	weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and , max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and 125-59 Total Depth 3103'. C.O.T. perf. int. (2 DJ/ft.) at 30 35,000# sand. RD pr. 1800# I.R. 31.2 BHM. Flush 31.00 Dropped 2 sets of 10 balls 1 understand that this plan of work must receive approach to the sand of t	weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and , max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and 25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000% sand. BD pr. 1800% I.R. 31.2 BHM. Flush 3160 Dropped 2 sets of 10 balls Lunderstand that this plan of work must receive approach to balls Company 21 Pasc Natural Cas Company Box 997	weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and , max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and 25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000 sand. BD pr. 1800 I.R. 31.2 BHM. Flush 3160 Dropped 2 sets of 10 balls I understand that this plan of work must receive approach to balls Dropped 2 sets of 3 balls Dropped 4	weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and 42-56; 3070-76 v/32,800 gallons water and 5 max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.
State names of and expected depths to objective sands; showing points, and 25-59 Total Depth 3103'. C.O.T perf. int. (2 DJ/ft.) at 30 35,000% sand. BD pr. 1800% I.R. 31.2 BHM. Flush 3160 Dropped 2 sets of 10 balls Lunderstand that this plan of work must receive approach to balls Company 21 Pasc Natural Cas Company Box 997	weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work) D. 3090'. Water fractured lictured Cliffs 42-56; 3070-76 v/32,800 gallons water and , max. pr. 1450%, avg. tr. pr. 1000%. gallons. Spotted 200 gallons MCA on perfs. each for 3 stages.