

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
Edna	
9. Well No.	
4	
10. Field and Pool, or Wildcat	
Devils Fork, Gallup	
12. County	
Rio Arriba	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-
2. Name of Operator
Merrion Oil & Gas Corporation
3. Address of Operator
P. O. BOX 1017, Farmington, New Mexico 87499
4. Location of Well
UNIT LETTER <u>H</u> <u>1733</u> FEET FROM THE <u>North</u> LINE AND <u>1147</u> FEET FROM
THE <u>East</u> LINE, SECTION <u>7</u> TOWNSHIP <u>24N</u> RANGE <u>6W</u> NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

6747' KB

12. County

Rio Arriba

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input checked="" type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

REMEDIAL WORK	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

ALTERING CASING	<input type="checkbox"/>
PLUG AND ABANDONMENT	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug and abandon Gallup Mesaverde side as follows:

1. Lay down rods.
2. Spot 25 sx plug across Gallup perfs from 5840 to 5540'.
3. Spot 10 sx plug across Mesaverde perfs 4500 - 4400'.
4. Spot 20 sx plug across Ojo Alamo 1950 - 1700'.
5. Spot 10 sx surface plug, erect dry hole marker.
6. Reclaim surface.

3a- 3150'-3050'- spot plug

4a- 250'-150'- spot plug @ Base of surface casing

all plugs must be inside and outside of the casing.

RECEIVED

FEB 22 1984

OIL CON. DIV.  
DIST. 3

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature]

TITLE Operation Manager

DATE 2/21/84

APPROVED BY [Signature]

TITLE Geologist

DATE 2/27/84

CONDITIONS OF APPROVAL, IF ANY: