

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **SF**
Lease No. **078877**
Unit **Canyon Largo**
14-08-001-1059

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Sandoil Frac.	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 27, 1963

Well No. **129** is located **1750** ft. from **N** line and **1750** ft. from **E** line of sec. **8**

SW/4 NE/4 Section 8

24N

6W

NMPM

Devils Fork Gallup

Rio Arriba

New Mexico

RECEIVED


The elevation of the derrick floor above sea level is **6713** ft.

JUN 28 1963

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

June 25, 1963 Total Depth 5833'. Clean Out Total Depth 5802'.
Sandoil fractured Gallup through perforated intervals 5769'-5787' (4Sh./Ft.) with
60,354 gals. Lease Crude and 70,000# sand, 0.05#/gal. Adomite Mark II. Breakdown
pressure 3300 psi; Maximum treating pressure 3900 psi; Average treating pressure
3400 psi. Injection Rate: 22.2 BPM.
Flush with 4200 gals. Lease Crude. Spotted 250 Gals. 15% Spearhead before fracture.



I understand that this plan or work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Products Company**

Address **Post Office Box 1560**

Farmington, New Mexico

ORIGINAL SIGNED BY: JOHN J. STROGER

By **Petroleum Engineer**