

(SUBMIT IN TRIPLICATE)

Indian Agency Alamogordo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Alamogordo Tribal

Lease No. Contract 111

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Subsequent Report of Sandfree Treatment</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 1st, 19 57

Well No. 8-N is located 990 ft. from N line and 990 ft. from E line of sec. 8

NE/4 NE/4 Sec. 8
(1/4 Sec. and Sec. No.)
S. Blanco FC Ext.
(Field)

24N 4W
(Twp.) (Range)
Rio Arriba
(County or Subdivision)

N.M.P.M.
(Meridian)
New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is 6710 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

9-8-57 TD 2869'. Cleaned out to 2832'. Perforated 2767-60' and 2808-20' with 4 jet shots per foot. Sandfraced with 25,500 gallons water and 30,000 sand, flushed with 3,000 gallons water. Breakdown pressure 2100#, treating pressure 1650-1700#. Dropped 60 rubber balls during treatment. Average injection rate 30.6 barrels per minute.

9-9-57 After 20 hours flowing 309 MCF/day.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company EL PASO NATURAL GAS COMPANY

Address Box 997

Farmington, New Mexico

By E. S. Oberly

Title Division Petroleum Engineer



