

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office SF

Leal & No. 078877

Uni Canyon Largo

14-08-001-1059

## SUNDRY NOTICES AND REPORTS ON WELLS

| NOTICE OF INTENTION TO DRILL                   | SUBSEQUENT REPORT OF WATER SHUT-OFF        | X |
|--|--|---|
| NOTICE OF INTENTION TO CHANGE PLANS            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING |   |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF     | SUBSEQUENT MEPORT OF ALTERING CASING       |   |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL | SUBSEQUER REPORT OF RE-DRILLING OR REPAIR  |   |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE        | SUBSEQUENT REPORT OF ABANDONMENT           |   |
| NOTICE OF INTENTION TO PULL OR ALIER CASING    | SUPPLEMENTARY WELL HISTORY                 |   |
| NOTICE OF INTENTION TO ABANDON WELL            |  |   |
| •  |  |   |

INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE OR OTHER DATA!

. . 19 63 May 2() 3x line and 890 ft. from W line of sec. Well No. 127 is located 1750 ft. from SW/4 NW/4 Section 8 24N **NMPM** (Two) (Meridian) (Maked and Sec. No.) Devils Fork Gallup Rio Arriba New Mexico (State or Territory) (County or Subcavision)

The elevation of the derrick floor above sea level is 6757 ft.

## DETAILS OF WORK

May 17, 1963 Total Depth 5851'.

Ran 184 joints, 4-1/2'', 10.50#, J-55 Casing (5839.54') set at 5850.54' with 75 sacks regular cement, 75 sacks Pozmix, 2% gel, 25# Gilsonite/-first stage.

Cemented 2nd stage through two-stage collar at 2493 with 50 sacks regular cement, 50 sacks Pozmix, 2% gel.

Held 1000#/30 Minutes.

Second Stage--Top of cement by temperature survey at 2000'. First Stage--Top of cement by calculation at 4681'.

Company

El Paso Natural Gas Products Company

Address

Post Office Box 1560

Farmington, New Mexico

By

Title

Petroleum Engineer