



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. SV 080420
Unit Mexico Fed "F"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<u>Production</u> <u>I</u>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	<u>Free</u> <u>I</u>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Report of perforation</u> <u>I</u>	
	<u>Report of plug back</u> <u>I</u>	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 27, 1960

Mexico Fed "F"
Well No. 1 is located 1490 ft. from N line and 990 ft. from W line of sec. 9

NM/A Section 9 24N 1W NMFM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Wildcat - P.C. Kio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 4-1/2" OD casing at 3795', cemented with 75 sacks regular cement 45 gal and 75 cu. ft. stratacrete.
Perforated 4 1/4" casing 3716-17' with 4 Lane Wells "F" gun bullets. Dry tested with snub, tested clay. Perforated 4 1/4" casing with 4 Lane Wells bullets per foot as follows: 3692-3702', 3704-08', 3710-12' and 3714-16'.
Sand fraced perforations 3692-3717'. Pumped down 4-1/2" OD casing 20,000# sand and 20,160 gallons water. Flushed with 9090 gallons water. BDP 1900#. Max. TP 1600#. Min. TP 1000#. Inj. rate.37 BPM.

Set Guilberson Magnesium bridge plug at 3675' and dumped 1 sz. cement on top, plugging back to 3663'.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced

Company Skelly Oil Company
Address Dr. 510
Farmington, New Mexico

By (Signed) P. E. Cosper
Title District Superintendent

