




LOCATE WELL CORRECTLY

U. S. LAND OFFICE **Jicarilla**SERIAL NUMBER **Tribal**LEASE OR PERMIT TO PROSPECT
Contract No. **69, Tract 131**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

LOG OF OIL OR GAS WELL

Company **Gulf Oil Corporation** Address **Box 2097, Denver 1, Colorado**
Lessor or Tract **Apache** Field **Otero - Pictured Cliffs** State **New Mexico**
Well No. **6** Sec. **7** T. **24N** R. **5W** Meridian **NMPN** County **Rio Arriba**
Location **1650** ft. **N** of **N** Line and **1650** ft. **E** of **E** Line of **Section 7** Elevation **6580'**
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed _____

Date **August 7, 1956**Title **Area Sup't. of Production**

The summary on this page is for the condition of the well at above date.

Commenced drilling **5-19**, 19**56** Finished drilling **6-15**, 19**56**

OIL OR GAS SANDS OR ZONES

(Denote gas by G)

No. 1, from **2320** to **2425** No. 4, from _____ to _____
No. 2, from _____ to _____ No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

No. 1, from **170** to **220** No. 3, from **1290** to **1390**
No. 2, from **950** to **1110** No. 4, from **1600** to **1970**

CASING RECORD

Size casing	Weight per foot	Threads per inch	Make	Amount	Kind of shoe	Cut and pulled from	Perforated		Purpose
							From—	To—	
8-5/8"	24 1/2	8 Round	EN	162'	-	-	-	-	Surface
4-1/2"	9 1/2	8 Round	EN	2445'	EN	-	2320'	2400'	Production
							2320'	2380'	
							2380'	2340'	

MUDDING AND CEMENTING RECORD

Size casing	Where set	Number sacks of cement	Method used	Mud gravity	Amount of mud used
8-5/8"	169'	100 sacks	Pump & plug	-	-
4-1/2"	2445'	125 sacks	"	-	-

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth set _____

Adapters—Material _____ Size **PSTD 2443'**, did not drill out casing plug.

SHOOTING RECORD

Size	Shell used	Explosive used	Quantity	Date	Depth shot	Depth cleaned out

TOOLS USED

Rotary tools were used from **0** feet to **2445** feet, and from _____ feet to _____ feet

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

DATES

_____, 19____ Put to producing **7-13**, 19**56**

The production for the first 24 hours was _____ barrels of fluid of which _____% was oil; _____% emulsion; _____% water; and _____% sediment. Gravity, °Bé. _____

If gas well, cu. ft. per 24 hours **6,236** Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. **694**

EMPLOYEES

Banner Drilling Company, Driller _____, Driller _____

_____, Driller _____, Driller _____

FORMATION RECORD

FROM—	TO—	TOTAL FEET	FORMATION
0	200'	200'	Unconsolidated sands and shales.
200'	500'	300'	Predominantly sandstone with minor intervals of shale.
500'	780'	280'	Predominantly shale.
780'	1110'	330'	Predominantly shale with a few water bearing sandstone from 30' to 50' thick.
1110'	2320'	1210'	Predominantly shale with occasional sandstone beds, coal seams in the lower portion - shale, gray to black, carbonaceous, sandy, soft sandstone, white, medium to coarse grain, loose with green to black inclusions.
2320'	2430'	110'	Predominantly sandstone, gray to grayish white, fine to medium grain, sub-rounded to sub-angular, well sorted, hard, medium porosity, with green, red, black inclusions - gas bearing sandstone.
2430'	2445'	15'	Lewis shale.

