1		

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

D no Ret t	DESERT MA	٠. ٠	14°K 33	0.7.
Form Ap	proved,			
Land Office	Sant	8	Po	
Lease No	0788	72	.	
Ca	מרוניות	¥.=	i Sécolos	the 44

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.	-	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALITER CASING		SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

		****		October 9	1963
Well No. 120 is loc	rated 1100 ft.	xx_{XX} from $\begin{bmatrix} x \\ S \end{bmatrix}$ line and	d 1650 ft. f	$\operatorname{rom}\left\{ \begin{array}{l} \mathbf{W} \\ \mathbf{W} \end{array} \right\}$ line of s	ec5
SW/4 Sec. 5 (% Sec. and Sec. No.)	24N	6W	N.A.P.M.	. ,	
(1/2 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)		
South Blanco Picture	d Cliffs	Rio Arriba		New Mexico	
(Field)	(Co	ounty or Subdivision)		(State or Territory)	
		11 m3			

The elevation of the derrick floor above sea level is 5624 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, comenting points, and all other important proposed work)

Spudded 9-29-63, drilled to 140'. Ran 4 joints 8 5/8", 24#, J-55 casing (125') set at 135' v/90 sacks regular cement, 2% calcium chloride circulated to surface.



I understand that this plan of work must receive approval in writing	by the Geological Survey before operations may be commenced.
CompanyEl Paso Natural Gas Company	
Address Box 990	
Farmington, New Mexico	By ORIGINAL SIGNED E.S. OBERLY
	Title Fetroleum Engineer