

OIL AND GAS CONSERVATION COMMISSION
ANNUAL REPORTS ON WELLS
Subject: _____ (Name as per Commission Rule 1106)

COMPANY SKELLY OIL COMPANY Drawer 510, Farmington, New Mexico

LEASE Farming "E" 3 TNE K 22 24N R 6W

DATE WORK REPORTED July 20, 1960 EC Undesignated Dakota

This is a Report (Check appropriate block) ☒ Revised of casing Shut-off

☐ Beginning Drilling work

☐ Plugging

Detailed account of work done, materials and quantity of materials used and results obtained.

Set 5-1/2" OD casing at 6857' with Halliburton "DV" tool at 3342'. First stage, cemented around shoe with 275 sacks regular cement and 275 sacks pozmix, 2% added gel. Temperature survey by B&R Service, Inc., indicated top of cement behind 5-1/2" OD casing at 4785'. Second stage, cemented through "DV" tool at 3342' with 250 sacks regular cement and 250 sacks pozmix, 2% added gel. Temperature survey by B&R Service, Inc., indicated top of cement behind 5-1/2" OD casing at 1670'.

FILL IN BELOW FOR REPAIR WORK

Original Well Data:

DF Elev. TD FB Perm Compl Date

Tbng Dia Tube Depth Casing Depth Casing String Depth

Perf Interval (s)

Open Hole Interval

RESULTS OF WORK DONE

Date of Test BEFORE AFTER

Oil Production, bbls per hr

Gas Production, Mcf per hr

Water Production, bbls per hr

Gas Oil Ratio, cu ft per bbl

Gas Well Potential, Mcf per day

Witnessed by (Company)

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge

Name


Name (Signed) P. E. Cooper

Title Supervisor Dist. # 3

Position District Superintendent

Date Aug 12 1960

Company Skelly Oil Company



STATE OF NEW MEXICO		
OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
NUMBER OF COPIES RECEIVED		
DIST. NO. 1111		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFF.		
TRANSPORTER	OIL	
	GAS	
PERMIT		
OPERATION		