

Form 9-331a
(Feb. 1951)

Section 4


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe

Lease No. 080472

Unit Cullins-Federal

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....		

RECEIVED
SEP 19 1957
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

..... September 16, 19 57

Cullins-Federal
Well No. 2 is located 1650 ft. from N line and 970 ft. from W line of sec. 4


Sec. 4 (Sec. and Sec. No.) 21-3 (Twp.) 3 (Range) N.M. (Meridian)
So. Blanco (Field) Blanco (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 7012 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

After setting 3392' of 5 1/2" casing on bottom at 3392' with 200 ex cement. Ran Temp. survey top of cement at 2050'. Tested 5 1/2" casing with 700 # for 30 min. Before and after washing out to 3372' P.B.T.D. Tested Ok. No break.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company AMERICAN OIL FIELD SERVICE COMPANY

Address P.O. BOX 633

BLANCO, TEXAS

By [Signature]
Title DIVISION SUPERINTENDENT