

(SUBMIT IN TRIPLICATE)

Indian Agency Alamogordo

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee Alamogordo Tribal
Lease No. Contract 111

X			

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		<u>Subsequent Report of Sandfract</u>	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 21st, 1957

Well No. 5-M is located 990 ft. from N line and 1090 ft. from E line of sec. 6

NW/4 NW/4 Sec. 6
(1/4 Sec. and Sec. No.)

24N
(Twp.)

4W
(Range)

N.M.P.M.
(Meridian)

S. Blanco PC Ext.
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)


The elevation of the derrick floor above sea level is 6870 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

6- 5-57 **FRIB 2975'. Perforated from 2916' to 2934' with 4 holes per foot. Sandfraced with 27,000 gallons water and 30,000 sand, flushed with 3,000 gallons water. Breakdown pressure 3000#, treating pressure 1500-1650#, average injection rate 99.9 BPM. Pumped 80 rubber balls in two stages during treatment.**

6- 6-57 After 15 hours flowing 264 MCF/day.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced

Company EL PASO NATURAL GAS COMPANY

Address Box 997

Farmington, New Mexico

By

Title Senior Petroleum Engineer

