

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Dugan Production Corp.

3. Address and Telephone No.

P.O. Box 420, Farmington, NM 87499 (505) 325-1821

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1550' FSL & 1490' FEL
J Sec. 33, T25N, R3W

5. Lease Designation and Serial No.

NM 06855

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

J.R. Anderson #1

9. API Well No.

30-039-05705

10. Field and Pool, or Exploratory Area

South Blanco PC

11. County or Parish, State

Rio Arriba, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Plugged well as follows:

1. Set cast iron bridge plug in 5-1/2" @ 3440'.
2. Spot 21 cu. ft. class "B" cement on top of bridge plug @3440'. Pictured Cliffs - Fruitland plug 3285 - 3440'.
3. Spot 21 cu. ft. class "B" cement @ 3120'. Ojo Alamo plug 1975 - 3120'.
4. Perforate 5-1/2" csg. @ 1530'. Spot 57 cu. ft. class "B" cement inside and outside casing. Nacimiento plug 1380' - 1530'.
5. Perforate 5-1/2" csg. @ 225'. Establish circulation out bradenhead. Fill 5-1/2" csg. and 9-5/8" annulus with 130 cu. ft. class "B" cement. Circulation cement out bradenhead. Surface plug 0 - 225'.

Job complete 7/25/97.

14. I hereby certify that the foregoing is true and correct

Signed

Title Vice-President

Date 8/6/97

(This space for Federal or State office use)

Approved by

Conditions of approval, if any:

Chief, Lands and Mineral Resources

Date SEP 2 1997

Surface restoration as per attached letter.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side