


(SUBMIT IN TRIPLICATE)

Land Office Santa Fe
Lease No. NM 06855
Unit Mexico Fed "H"

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	<u>Production</u> X
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Report of perforations</u>	X
	<u>Report of sand frac</u>	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 11, 1960

Mexico Fed "H"
Well No. 1 is located 790 ft. from [N] line and 790 ft. from [W] line of sec. 34
NW/4 Section 34 25N 3W NMPH
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
South Blanco - P. C. Ext. Rio Arriba County New Mexico
(Field) (County or Subdivision) (State or Territory)

RECEIVED

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

TD 3627'. Ran 2-7/8" OD tubing, set at 3642' with 150 sacks, 50% regular cement and 50% poxmix, 2% added gal. Temperature survey indicated top of cement at 2900'. Perforated 2-7/8" OD tubing with 4 Lane Wells Sidewinder jets per foot as follows:
3540-3570' (90') 120 holes
3577-3580' (3') 12 holes
Pumped down 2-7/8" OD tubing, 15,000# of 20/40 sand and 17,766 gallons water. BDP 2000#, Max. T.P. 2000#, Min. T.P. 1800#. Flushed with 1260 gallons water. Injection rate 16.4 BPM. Used 40 rubber frac balls in treatment. Shut down pressure 200#. Well on vacuum in 5 minutes after pumps shut down.

U. S. GEOLOGICAL SURVEY
WASHINGTON, NEW MEXICO

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company SKELLY OIL COMPANY

Address Drawer 510

Farmington, New Mexico

By [Signed] P. E. Cosper

Title District Superintendent

RECEIVED
AUG 15 1960
OIL CON. COM
DIST. 3