



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Antelope  
Lease No. 44-7701  
Unit Lytle Antelope

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Report of 1st and Preceing

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 17, 1957

Well No. 2 is located 1450 ft. from N line and 990 ft. from W line of sec. 19  
1/4 Section 19 25N 37 N.W. 1/4  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
A. Blanco - J.C. (ext.) Pio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

perforated 7" casing 3595-3611' & 3615-3624' with 4 nolex jet shots per ft. Total of 24', 96 shots. Included in above perforations is 1' 3623-24' which was perforated to test cement job. Cement job tested 1.5.

Drilled 7" casing perforations, pictured G.I. formation, 3595-3611' and 3615-3624' with 40,000 gal. sand & 40,000 gals. water. B.T. 2000, Max. T. 3500, Min. T. 2000, Int. rate 34.2 MIN.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company \_\_\_\_\_

Address \_\_\_\_\_

By \_\_\_\_\_

Title District Superintendent