

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

Jicarilla Contr. #127

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Apache

9. WELL NO.

100

10. FIELD AND POOL, OR WILDCAT

Undesignated11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 3-T24N-R4W****N.M.P.M.**

12. COUNTY OR PARISH

Rio Arriba

13. STATE

N.M.

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

Manning Gas & Oil Company

3. ADDRESS OF OPERATOR

**102 Continental Oil Building,
1755 Glenarm Place, Denver, Colorado 80202**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface**435' from North Line, 475' from East line.
Sec. 3-T24N-R4W**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6876' G.L., 6888'DF, 6889'KB

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-4-72 T. D. 260'**Spud well 1-4-72. Ran 6 jts. 8-5/8", 23.0#/ft, X-42 casing (242')
Set at 255' with 175 sacks Class "A" Cement with 2% Calcium Chloride.
Cement circulated to surface. Tested casing with 500 psig. Test OK.****1-23-72 TD 7602'****Ran 236 jts., 4 1/2" casing (31 jts, 11.60#/ft, 981.76', 205 jts.,
10.50 #/ft 6599.56', cementing equipment, 5.22' for a total of
7586.54'). Set at 7600'. Two stage tool at 5504'. Cemented with,
1st Stage - 500 gallons mud flush followed by 475 sacks 50-50
Pozmix "A" with 6 1/2 lbs gilsonite per sack, 0.5% CFR-2 and 6 pounds
salt per sack. Tested casing with 2000 psig. Test OK. 2nd stage -
600 sacks Liteweight cement followed by 50 sacks Class "A" cement.
Tested casing with 2000 psig. Test OK. Calculated top of cement:
1st stage - 6200'. 2nd stage - 2900'.**

18. I hereby certify that the foregoing is true and correct

SIGNED

Erroll N. Walsh

TITLE

**Petroleum Engineer
Consultant**

DATE

2-4-72

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.