

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. GIL WELL ☒ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO. JIC #9
2. NAME OF OPERATOR Anerada Hess Corporation, Attn: Drilling Services		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache
3. ADDRESS OF OPERATOR P.O. Box 2040, Tulsa, Oklahoma 74102		7. UNIT AGREEMENT NAME (Lease Contract #9)
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At Surface 1650' PSL & 1820' FEL		8. FARM OR LEASE NAME J. Apache "A"
14. PERMIT NO.		9. WELL NO. 7
15. ELEVATIONS (Show whether DF, RT., GR., etc.) Gr. 6961'		10. FIELD AND POOL, OR WILDCAT Otero/Gallup: Basin/Dakota
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26, T25N, R5W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SEUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Logging & csg. setting ☒	
(Other) ☐		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	


17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Driller's TD 7650'; Loggers TD 7641'

After setting, cementing & testing 9-5/8"OD surface casing (Re: Sundry Report dated Oct. 14, 1975) drilled a 7-7/8" hole out under surface csg. to TD of 7650', circ. and conditioned hole @ 7,650' for 2 1/2 hrs. 11/1/75, rigged up Dresser-Atlas, run FDC/CNC with caliber & GR as follows: Formation Density 7641-2000', GR 7641 to surface and caliber 7641 to 381', run dual laterolog 7641 to 381' (381' btm. of 9-5/8" surface csg.), check TD at 7641', finished logging @ 6 PM 11/2/75, trip in with bit, condition hole for 5 1/2" csg., trip out, rig up and run 60 jts. of 5 1/2"OD 15.5# K-55 new casing and 136 jts. of 5-9/16"OD 15.63# X-52 new casing, Baker float collar @ 7617', DV collars @ 5984 and 2518', casing set at 7649' @ 4:30 PM Nov. 3, '75, Halliburton cemented 5 1/2" csg. with a total of 575 sx. 50/50 pozmix 1st. stage, return while cementing and total of 975 sx. lite wate on final stages, max. pumping pressure 2000#. WOC at 8 AM 11/4/75. Released drilling rig @ 6 PM 11/4/75.

Will move in completion rig approx. Nov. 10, 1975 for a Gallup/Dakota completion.

Geological Sample Tops: Greenhorn 7210'; Graneros 7240'; Graneros Sand 7300'; Dakota 7440':
Est. top of Gallup @ 5125'



18. I hereby certify that the foregoing is true and correct

SIGNED *E. N. J. J.*

TITLE Supervisor Test Drg. Adm. Sec. DATE 11/5/75

(This space for Federal or State office use)

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

CA