orm 9-331 May 1963)	UNITED STATES PARTMENT OF THE INTERI	SUBMIT IN TRIPLICATE®	Form approv. Budget Bures	au No. 42-R1424.
DLI	GEOLOGICAL SURVEY	TOR verse side)	1	
			Lease Contract //11 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			Jicarilla Apache	
OIL GAS GA			7. UNIT AGREEMENT NA	AME
WELL WELL X	OTHER			
2. NAME OF OPERATOR Amerada Hess Corporation			8. FARM OR LEASE NAME	
3. ADDRESS OF OPERATOR			J. Apache "B"	
P.O. Drawer 817, Seminole, Texas 79360			9. WELL NO.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements *			15	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface			10. FIELD AND POOL, OR WILDCAT Otero: Dakota & Pictured Cli	
1630' FSL and 1465' FWL			11. SEC., T., R., M., OR BLK. AND	
			SURVEY OR AREA	
			Sec. 30, T24N, R5W	
4. PERMIT NO.	15. ELEVATIONS (Show whether DF	RT, GR, etc.)	12. COUNTY OR PARISH	1 13 STATE
6561' Gr.		, , , , , , , , , , , , , , , , , , , ,	Rio Arriba	New Mexico
	neck Appropriate Box To Indicate N of Intention to: FULL OR ALTER CASING		UENT REPORT OF:	WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING C.	ASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONME	NT*
REPAIR WELL	(Norm: Percet results		4	
(Other)	Completion of Recomp		letion Report and Log for	rm.)
7. DESCRIBE PROPOSED OR COMPI proposed work. If well nent to this work.) *	LETED OPERATIONS (Clearly state all pertinen is directionally drilled, give subsurface local	it details, and give pertinent dates, tions and measured and true vertice	, including estimated dat al depths for all marker	te of starting any s and zones perti-
TD 6,760' by Dr.	iller; 6,757 by Loggers			·
drilled a 7-7/8" Dual Induction L and caliper but to bottom and co. at 6758 W/a tota	ut under 9-5/8"(1) surface hole to 6,760', cond. hole aterolog 6,755 to 375', at was unable to get below 12 nd. hole for 5½" csg. Rur 1 of 2025 sx. cement in 3 6715' 8/22/76 by R.J. goo	le and logged by Dress ttempt to run Comp. Fo 400', run bit and rem n, set and cemented 5	ser-Atlas 8/20/ orm Density neu med out bridge, ½"OD 15.5# K-55 lars @ 5005 & 3 ement job with	/76 with itron W/GR , finish trip 5 new casing 3399 and top of low-
float collar at dense cement es	t. @ 700'. Rigged down Ca	actus Drlg. Co. and re	eleased rig at	3 AM 8/23/76
dense cement es	t. @ 700'. Rigged down Ga	actus Drlg. Co. and re		3 AM 8/23/76
dense cement es	t. @ 7001. Rigged down Ca	actus Drlg. Co. and re	e .	3 AN 8/23/76