

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
3. LEASE DESIGNATION AND SERIAL NO.

Contract #11

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. Apache "B"

9. WELL NO.

15

10. FIELD AND POOL, OR WILDCAT

Basin - Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30, T24N, R5W

12. COUNTY OR PARISH 13 STATE

Rio Arriba New Mex.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Amerada Hess Corporation

3. ADDRESS OF OPERATOR

Drawer "D", Monument, New Mexico 88265

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1630' FSL and 1465' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6561' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

June 1979

Set rods, pump and 2-3/8" tbg. Ran 5 1/2" Baker pkr. on 2-3/8" tbg. and
pkr. @ 6464'. Ran flowing press. gradients. Dresser Atlas ran Sonand-
temperature log fr. 6597' to 6471'. Dowell acidized Dakota zone 5 1/2" csg.
perf. fr. 6528' to 6538' & fr. 6558' to 6578' w/3000 gal. 12% HCL and 3% HF
acid w/additives and 700 SCF nitrogen per bbl. Swabbed load. Re-ran tbg.,
pump and rods and resumed prod.

Test of 6-20-79 Flowed and pumped 5 b.o. and gas @ rate of 233 MCFPD.

18. I hereby certify that the foregoing is true and correct

SIGNED E. B. Baker

TITLE Supv. Adm. Ser.

DATE July 5, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: