SUBMIT IN TRIPLICATE* UNITED STATES

Form approved.

	DEPARTMENT OF THE INTERIOR (Other instructions on re-	5. LEASE DESIGNATION LSe. Contr		
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE Jicarilla Ap		
1.	GIL GAS WELL X OTHER	7. UNIT AGREEMENT NAM	16	
2.	Amerada Hess Corporation	8. FARM OR LEASE NAME J. Apache "A"		
3.	P.O. Drawer 817, Seminole, Texas 79360	9. WELL NO.		
4.	At surface 960 FSL and 1690 FWL	10. FIELD AND FOOL, OR WILDCAT Otero: Pictured Cliffs and Chacra 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 26, T25N, R5W		
14.	Gr. 6910'	12. COUNTY OR PARISH Rio Arriba	13. STATE New Mexico	
16,	Check Appropriate Box To Indicate Nature of Notice, Report, or Ot	her Data		


NOTICE OF INTENTION TO:			SUBSEQUENT REPORT OF:		
TEST WATER SHUT-OFF		PULL OR ALTER CASING		WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT		MULTIPLE COMPLETE		FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE		ABANDON*	<u> </u>	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL		CHANGE PLANS		(Other)	
(Other)				(Note: Report results of m Completion or Recompletion	ultiple completion on Well Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 4,020' by Driller; 4,008' by Logger

Drilled a 7-7/8" hole out under 8-5/8" surface casing at 1 AM 9/28/76(Re: Sundry Notice Report dated 9/28/76) to total depth of 4,020', cond. hole to log, 10/3/76 and logged well by Dresser-Atlas, DILL-SP-GR 4006 to surface, CN FD W/caliper and GR 4006 to 2241, checked btm. at 4,008 by wire line measurement, fin. logging at 7 PM 10/3/76. Condition hole, run, set and cemented $4\frac{1}{2}$ "OD 10.5# K-55 new casing at 4,018' (insert float valve at 3978') with a total of 755 sx. Lo-Dense and Class C cement by B.J., finished cementing at 12 noon 10/4/76. Set slips, cut off $4\frac{1}{2}$ " csg., N.D. BOPs and released Cactus Drlg. Co. rig at 2 PM, 10/4/76. (Had good circulation while cementing above $4\frac{1}{2}$ " csg.)

Will move in a completion unit when one is available in the near future.



*See Instructions on Reverse Side