

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ WELL GAS ☒ WELL OTHER ☐
2. NAME OF OPERATOR  
Amerada Hess Corporation
3. ADDRESS OF OPERATOR  
Drawer D, Monument, New Mexico 88265
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
890' FNL and 890' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6877' GR (Ungraded)

5. LEASE DESIGNATION AND SERIAL NO.

Lse. Contract #9

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

J. Apache "A"

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Otero - Dakota

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 36, T25N, R5W

12. COUNTY OR PARISH

13. STATE

Rio Arriba

New Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

June 1979

Pulled 1½" tbg. Ran 5½" Baker Model R pkr. on 2-3/8" tbg. & set pkr. @ 7177'. Dresser Atlas ran GR-CCL log fr. 7150' to 7384' & differential temp. log fr. 6900' to 7360'. Dowell acidized Dakota zone thru 5½" csg. perf. fr. 7302' to 7353' w/2200 gal. 12% HCl & 3% HF acid w/additives & 700 SCF nitrogen per bbl. using ball sealers. Swabbed load. Pulled 2-3/8" tbg. & pkr. Re-ran 1½" tbg. set @ 7348 & resumed prod.

Test of 7-6-79 Flowed 22 b.o. & 664 MCFPD, TP 1170#, CP 1170#.

18. I hereby certify that the foregoing is true and correct

SIGNED

*E. B. Fisher*

TITLE

Supv. Adm. Ser.

DATE

July 6, 1979

(This space for Federal or State office use)


APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side



JUL 10 1979

U. S. GEOLOGICAL SURVEY  
DENVER, COLO.