

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. NAME OF OPERATOR
Continental Oil Company
3. ADDRESS OF OPERATOR
Box 460, Hobbs, N.M. 88240
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1190' FNL & 1850' FWL of Sec 11

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7383' GR

5. LEASE DESIGNATION AND SERIAL NO.

Contract No. 121

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Jicarilla Apache

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

AXI Apache "N"

9. WELL NO.

12

10. FIELD AND POOL, OR WILDCAT

S. Blanco Pictured Cl. ffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 11 T25N R4W

12. COUNTY OR PARISH

Rio Arriba N.M.

13. STATE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Set 8 5/8" Casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 9:30 pm, 6-26-77. Drilled a 12 1/4" hole to 518'. Set 12 jts. 8 5/8", 24#, STXC casing at 518'. Cemented w/160 sx Class 'B' w/490 gel, 2% CaCl2, then w/160 sx Class 'B' w/2% CaCl2. Plugged down at 10:45 am. Pressure tested to 1000 pounds. Ok. Drilled ahead w/ 7 7/8" hole.

18. I hereby certify that the foregoing is true and correct.

SIGNED

*John A. Butterfield*TITLE *ADMIN. SUPV.*

DATE

7-6-77

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

1. C. C. N.M. 2. MTL BEA. Exxon 7:10