

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. Contract No. 127
2. NAME OF OPERATOR Cotton Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Jicarilla Apache
3. ADDRESS OF OPERATOR		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1600' FSL, 1850' FEL		8. FARM OR LEASE NAME Apache
14. PERMIT NO.		9. WELL NO. 21
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6779'GR, 6789'DF, 6790'KB		10. FIELD AND POOL, OR WILDCAT So. Blanco D.C.
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4-T24N-R4W N.M.P.M.
		12. COUNTY OR PARISH Rio Arriba
		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☒
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-22-77 Spud Well. TD 197'

Ran 4 jts., 8 5/8", 24.0 lb., K-55 casing (183.74'). Set at 194.74' with 200 sacks Class "B" Cement with 2% CaCl and 1/4 lb. Flocele per sack. Cement circulated. Test with 500 psig. Test OK.

7-26-77 TD 2920'

Ran 71 jts., 4 1/2", 10.50 lb., K-55 casing (2911.44'). Set at 2920.44' with 200 sacks 50/50 Pozmix. Calculated top of cement 2150'.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ewell N. Walsh
Ewell N. Walsh, P. E.

TITLE

President, Walsh Engr. & Prod. Corporation

DATE

July 28, 1977

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side